

## Advance Information

MPC7447ANXPNS

Rev. 0, 2/2004

MPC7447A Part Number  
Specification for the  
MC7447AnnnNx Series

Motorola Part  
Numbers Affected:

MC7447AHX1000NB

MC7447AHX1167NB

This document describes part-number-specific changes to recommended operating conditions and revised electrical specifications, as applicable, from those described in the general *MPC7447A RISC Microprocessor Hardware Specifications*. The MPC7447A is a PowerPC™ microprocessor.

Specifications provided in this document supersede those in the *MPC7447A RISC Microprocessor Hardware Specifications*, Rev. 0 or later, for the part numbers listed in Table A only. Specifications not addressed herein are unchanged.

Note that headings and table numbers in this document are not consecutively numbered. They are intended to correspond to the heading or table affected in the general hardware specification.

Part numbers addressed in this document are listed in Table A.

**Table A. Part Numbers Addressed by this Data Sheet**

Motorola Part Number	Operating Conditions			Significant Differences from Hardware Specification
	CPU Frequency (MHz)	V <sub>DD</sub>	T <sub>j</sub> (°C)	
PPC7447AHX1000NB	1000	1.1 V ± 50 mV	0 to 105	Modified core frequency and voltage to reduce power consumption, modified processor bus clock frequency and AC timing.
PPC7447AHX1167NB	1167			

**Note:** The P prefix in a Motorola part number designates a "Pilot Production Prototype" as defined by Motorola SOP 3-13. These parts have only preliminary reliability and characterization data. Before pilot production prototypes may be shipped, written authorization from the customer must be on file in the applicable sales office acknowledging the qualification status and the fact that product changes may still occur while shipping pilot production prototypes.

PRELIMINARY—SUBJECT TO CHANGE WITHOUT NOTICE

**For More Information On This Product,  
Go to: [www.freescale.com](http://www.freescale.com)**

## 1.2 Features

This section summarizes changes to the features of the MPC7447A described in the *MPC7447A RISC Microprocessor Hardware Specifications*.

- Power management
  - 1.1-V processor core

## 1.4 General Parameters

- Core power supply: 1.1 V  $\pm$  50 mV DC nominal

### 1.5.1 DC Electrical Characteristics

Table 4 provides the recommended operating conditions for the MPC7447A part numbers described herein.

**Table 4. Recommended Operating Conditions <sup>1</sup>**

Characteristic	Symbol	Recommended Value	Unit	Notes
Core supply voltage	V <sub>DD</sub>	1.1 V $\pm$ 50 mV	V	
PLL supply voltage	AV <sub>DD</sub>	1.1 V $\pm$ 50 mV	V	2

**Note:**

1. These are the recommended and tested operating conditions. Proper device operation outside of these conditions is not guaranteed.
2. This voltage is the input to the filter discussed in *MPC7447A RISC Microprocessor Hardware Specifications*, Section 1.9.2, “PLL Power Supply Filtering,” and not necessarily the voltage at the AV<sub>DD</sub> pin, which may be reduced from V<sub>DD</sub> by the filter.

Table 7 provides the power consumption for the MPC7447A part numbers described herein. For information regarding power consumption when dynamic frequency switching (DFS) is enabled, see the *MPC7447A RISC Microprocessor Hardware Specifications*.

**Table 7. Power Consumption for MPC7447A**

	Processor (CPU) Frequency		Unit	Notes
	1000 MHz	1167 MHz		
<b>Full-Power Mode</b>				
Typical	8.0	9.2	W	1, 2
Maximum	11.5	13.0	W	1, 3
<b>Nap Mode</b>				
Typical	1.3	1.3	W	1, 2
<b>Sleep Mode</b>				
Typical	1.3	1.3	W	1, 2
<b>Deep Sleep Mode (PLL Disabled)</b>				
Typical	1.2	1.2	W	1, 2

**Notes:**

1. These values apply for all valid processor buses. The values do not include I/O supply power ( $OV_{DD}$ ) or PLL supply power ( $AV_{DD}$ ).  $OV_{DD}$  power is system dependent but is typically < 5% of  $V_{DD}$  power. Worst case power consumption for  $AV_{DD}$  < 3 mW.
2. Typical power is an average value measured at the nominal recommended  $V_{DD}$  (see Table 4) and 65°C while running the Dhrystone 2.1 benchmark and achieving 2.3 Dhrystone MIPs/MHz.
3. Maximum power is the average measured at nominal  $V_{DD}$  and maximum operating junction temperature (see Table 4) while running an entirely cache-resident, contrived sequence of instructions which keep all the execution units maximally busy.
4. Doze mode is not a user-definable state; it is an intermediate state between full-power and either nap or sleep mode. As a result, power consumption for this mode is not tested.

## 1.5.2 AC Electrical Characteristics

Table 8 provides the clock AC timing specifications for the MPC7447A part numbers described herein.

**Table 8. Clock AC Timing Specifications**

At recommended operating conditions. See Table 4.

Characteristic	Symbol	Maximum Processor Core Frequency				Unit	Notes
		1000 MHz		1167 MHz			
		Min	Max	Min	Max		
Processor frequency	$f_{core}$	500	1000	500	1167	MHz	1, 2
VCO frequency	$f_{VCO}$	1000	2000	1000	2333	MHz	1

**Notes:**

1. **Caution:** The SYSCLK frequency and PLL\_CFG[0:4] settings must be chosen such that the resulting SYSCLK (bus) frequency, CPU (core) frequency, and PLL (VCO) frequency do not exceed their respective maximum or minimum operating frequencies. Refer to the PLL\_CFG[0:4] signal description in *MPC7447A RISC Microprocessor Hardware Specifications*, Section 1.9.1, "PLL Configuration," for valid PLL\_CFG[0:4] settings.
2. **Caution:** If dynamic frequency switching (DFS) is enabled, the SYSCLK frequency and PLL\_CFG[0:4] settings must be chosen such that the resulting processor frequency is greater than or equal to the minimum core frequency.

### 1.5.2.2 Processor Bus AC Specifications

Devices described by this part number specification conform to the processor bus AC timing specifications provided in the *MPC7447A RISC Microprocessor Hardware Specifications*. Please refer to that document for this information.

## 1.11 Ordering Information

### 1.11.1 Part Numbers Addressed by This Specification

Table 16 provides the ordering information for the MPC7447A parts described in this document.

Table 16. Part Marking Nomenclature


<i>xxx</i>	<i>7447A</i>	<i>HX</i>	<i>nnnn</i>	<i>N</i>	<i>X</i>
Product Code	Part Identifier	Package	Processor Frequency <sup>1</sup>	Application Modifier	Revision Level
MC	7447A	HX = HCTE	1000 1167	N: 1.1 V ± 50 mV 0 to 105°C	B:1.1: PVR = 8003 0101

**Notes:**

1. Processor core frequencies supported by parts addressed by this specification only. Parts addressed by other specifications may support other maximum core frequencies.

### 1.11.3 Part Marking

Parts are marked as the example shown in Figure 22.



**Notes:**

- AWYYYYWW is the test code.
- MMMMMM is the M00 (mask) number.
- YWWLAZ is the assembly traceability code.

Figure 22. Part Marking for BGA Device

## Document Revision History

Table B provides a revision history for this part number specification.

**Table B. Document Revision History**

Rev. No.	Substantive Change(s)
0	Initial release.

THIS PAGE INTENTIONALLY LEFT BLANK

# Freescale Semiconductor, Inc.

## HOW TO REACH US:

### USA/EUROPE/LOCATIONS NOT LISTED:

Motorola Literature Distribution  
P.O. Box 5405, Denver, Colorado 80217  
1-480-768-2130  
(800) 521-6274

### JAPAN:

Motorola Japan Ltd.  
SPS, Technical Information Center  
3-20-1, Minami-Azabu Minato-ku  
Tokyo 106-8573 Japan  
81-3-3440-3569

### ASIA/PACIFIC:

Motorola Semiconductors H.K. Ltd.  
Silicon Harbour Centre, 2 Dai King Street  
Tai Po Industrial Estate, Tai Po, N.T., Hong Kong  
852-26668334

### TECHNICAL INFORMATION CENTER:

(800) 521-6274

### HOME PAGE:

[www.motorola.com/semiconductors](http://www.motorola.com/semiconductors)

Information in this document is provided solely to enable system and software implementers to use Motorola products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document.

Motorola reserves the right to make changes without further notice to any products herein.

Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part.



Motorola and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. digital dna is a trademark of Motorola, Inc. The described product is a PowerPC microprocessor. The PowerPC name is a trademark of IBM Corp. and used under license. All other product or service names are the property of their respective owners. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

© Motorola, Inc. 2004

MPC7447ANXPNS

**For More Information On This Product,  
Go to: [www.freescale.com](http://www.freescale.com)**