



CONNOR-WINFIELD CORPORATION



AURORA, IL. 60505

PHONE (630) 851-4722

FAX (630) 851-5040

14 PIN DIP HCMOS

SPECIFICATIONS			MPH61	MPH62	MPH63	MPH64
Frequency Range			250KHz to 50MHz			
Frequency Stability			±25ppm	±50ppm	±100ppm	±20ppm
			(Inclusive of calibration tolerance at 25°C, operating temperature range, input voltage change, load change, aging, shock and vibration)			
Temperature Range			−40°C to +85°C			
Output	Waveform		HCMOS Squarewave			
	Load		15pF			
	Voltage	Voh	4.5V Minimum			
		Vol	0.5V Maximum			
	Current	Ioh	−4.0mA			
		Iol	4.0mA			
	Duty Cycle		48/52 measured at 2.5V			
	Rise/Fall Time		10nS Maximum			
Start Up Time			10mS Maximum			
Supply Voltage			+5Vdc ±10%			
Supply Current			25mA Maximum			
Package			All metal, hermetically sealed, welded package			



PIN	CONNECTION
1	N/C
7	GROUND (CASE)
8	OUTPUT
14	(+) SUPPLY

Dimensional Tolerance ±.005

Specifications subject to change without notice

BULLETIN #: HC098
PAGE 1 OF 1REV: 00
DATE: 5/13/95

ISSUED BY: _____

www.DataSheet4U.com