




MPSA44H

NPN SILICON TRANSISTOR

HIGH VOLTAGE TRANSISTOR

FEATURES

- * Collector-Emitter Voltage: $V_{CE0}=400V$
- * Collector Current up to 300mA



ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
MPSA44HL-AB3-R	MPSA44HG-AB3-R	SOT-89	B	C	E	Tape Reel
MPSA44HL-T92-B	MPSA44HG-T92-B	TO-92	E	B	C	Tape Box
MPSA44HL-T92-K	MPSA44HG-T92-K	TO-92	E	B	C	Bulk
MPSA44HL-T92-R	MPSA44HG-T92-R	TO-92	E	B	C	Tape Reel

MPSA44HL-AB3-R	(1)Packing Type (2)Package Type (3)Lead Free	(1) B: Tape Box, K: Bulk, R: Tape Reel (2) AB3: SOT-89, T92: TO-92 (3) G: Halogen Free, L: Lead Free
----------------	--	--

■ ABSOLUTE MAXIMUM RATING

PARAMETER		SYMBOL	RATINGS	UNIT
Collector-Base Voltage		V_{CBO}	800	V
Collector-Emitter Voltage		V_{CEO}	400	V
Emitter-Base Voltage		V_{EBO}	6	V
Collector Current		I_C	300	mA
Collector Dissipation	SOT-89	P_C	500	mW
	TO-92		625	
Junction Temperature		T_J	125	°C
Operating Temperature		T_{OPR}	-20 ~ +85	°C
Storage Temperature		T_{STG}	-40 ~ +150	°C







Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS ($T_J=25^{\circ}\text{C}$, unless otherwise specified)



PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector-Base Breakdown Voltage	BV_{CBO}	$I_C=100\mu\text{A}$, $I_E=0$	800			V
Collector-Emitter Breakdown Voltage	BV_{CEO}	$I_C=1\text{mA}$, $I_B=0$	400			V
Emitter-Base Breakdown Voltage	BV_{EBO}	$I_E=100\mu\text{A}$, $I_C=0$	6			V
Collector Cutoff Current	I_{CBO}	$V_{CB}=400\text{V}$, $I_E=0$			0.1	μA
Collector Cutoff Current	I_{CEO}	$V_{CE}=400\text{V}$, $I_B=0$			0.5	μA
Emitter Cutoff Current	I_{EBO}	$V_{EB}=4\text{V}$, $I_C=0$			0.1	μA
ON CHARACTERISTICS						
DC Current Gain (Note)	h_{FE}	$V_{CE}=10\text{V}$, $I_C=1\text{mA}$	40		240	
		$V_{CE}=10\text{V}$, $I_C=10\text{mA}$	82		240	
		$V_{CE}=10\text{V}$, $I_C=50\text{mA}$	45		240	
		$V_{CE}=10\text{V}$, $I_C=100\text{mA}$	40		240	
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	$I_C=1\text{mA}$, $I_B=0.1\text{mA}$			0.4	V
		$I_C=10\text{mA}$, $I_B=1\text{mA}$			0.5	
		$I_C=50\text{mA}$, $I_B=5\text{mA}$			0.75	
Base-Emitter Saturation Voltage	$V_{BE(SAT)}$	$I_C=10\text{mA}$, $I_B=1\text{mA}$			0.75	V
SMALL-SIGNAL CHARACTERISTICS						
Current Gain Bandwidth Product	f_T	$V_{CE}=20\text{V}$, $I_C=10\text{mA}$, $f=100\text{MHz}$	50			MHz
Output Capacitance	C_{OB}	$V_{CB}=20\text{V}$, $I_E=0$, $f=1\text{MHz}$			7	pF

Note: Pulse test: $P_W < 300\mu\text{s}$, Duty Cycle $< 2\%$

■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS(Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.