

MR870 MR871 MR872 MR874 MR876



MOTOROLA

Designers Data Sheet

STUD MOUNTED FAST RECOVERY POWER RECTIFIERS

... designed for special applications such as dc power supplies, inverters, converters, ultrasonic systems, choppers, low RF interference, sonar power supplies and free wheeling diodes. A complete line of fast recovery rectifiers having typical recovery time of 150 nanoseconds providing high efficiency at frequencies to 250 kHz.

Designer's Data for "Worst Case" Conditions

The Designers Data sheets permit the design of most circuits entirely from the information presented. Limit curves — representing boundaries on device characteristics — are given to facilitate "worst case" design.

MAXIMUM RATINGS

Rating	Symbol	MR870	MR871	MR872	MR874	MR876	Unit
Peak Repetitive Reverse Voltage	V_{RRM}	50	100	200	400	600	Volts
Working Peak Reverse Voltage	V_{RWM}						
DC Blocking Voltage	V_R						
Non-Repetitive Peak Reverse Voltage	V_{RSM}	75	150	250	450	650	Volts
RMS Reverse Voltage	$V_R(RMS)$	35	70	140	280	420	Volts
Average Rectified Forward Current (Single phase, resistive load, $T_C = 100^\circ C$)	I_O	50					Amps
Non-Repetitive Peak Surge Current (surge applied at rated load conditions)	I_{FSM}	400					Amps
Operating Junction Temperature Range	T_J	-65 to +160					$^\circ C$
Storage Temperature Range	T_{stg}	-65 to +175					$^\circ C$

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Case	$R_{\theta JC}$	0.8	$^\circ C/W$

ELECTRICAL CHARACTERISTICS

Characteristic	Symbol	Min	Typ	Max	Unit
Instantaneous Forward Voltage ($I_F = 157$ Amp, $T_J = 160^\circ C$)	V_F	—	1.3	1.6	Volts
Forward Voltage ($I_F = 50$ Amp, $T_C = 25^\circ C$)	V_F	—	1.1	1.4	Volts
Reverse Current (rated dc voltage) $T_C = 25^\circ C$ $T_C = 100^\circ C$	I_R	—	25 1.0	50 2.0	μA mA

REVERSE RECOVERY CHARACTERISTICS

Characteristic	Symbol	Min	Typ	Max	Unit
Reverse Recovery Time ($I_F = 1.0$ Amp to $V_R = 30$ Vdc, Figure 16) ($I_{FM} = 36$ Amp, $di/dt = 25$ A/ μs , Figure 17)	t_{rr}	—	150 240	200 400	ns
Reverse Recovery Current ($I_F = 1.0$ Amp to $V_R = 30$ Vdc, Figure 16)	$I_{RM}(REC)$	—	2.0	3.0	Amp


MECHANICAL CHARACTERISTICS

CASE: Welded, hermetically sealed
FINISH: All external surfaces
corrosion resistant
and readily solderable

POLARITY: Cathode to Case
WEIGHT: 17 grams (approximately)
STUD TORQUE: 25 in. lbs.

FAST RECOVERY POWER RECTIFIERS

**50-600 VOLTS
50 AMPERES**



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	16.94	17.45	0.669	0.687
B	—	16.94	—	0.667
C	—	11.43	—	0.450
D	—	9.53	—	0.375
E	2.92	5.08	0.115	0.200
F	—	2.03	—	0.080
J	10.72	11.51	0.422	0.453
K	—	25.40	—	1.000
L	3.86	—	0.156	—
P	5.59	6.32	0.220	0.249
Q	3.56	4.45	0.140	0.175
R	—	20.16	—	0.794
S	—	2.26	—	0.089

NOTES:

- DIM "P" IS DIA.
- CHAMFER OR UNDERCUT ON ONE OR BOTH ENDS OF HEXAGONAL BASE IS OPTIONAL.
- ANGULAR ORIENTATION AND CONTOUR OF TERMINAL ONE IS OPTIONAL.
- THREADS ARE PLATED.
- DIMENSIONING AND TOLERANCING PER ANSI Y14.5, 1973.

CASE 257-01
DO-5

FIGURE 1 – FORWARD VOLTAGE






FIGURE 2 – MAXIMUM SURGE CAPABILITY



NOTE 1



To determine maximum junction temperature of the diode in a given situation, the following procedure is recommended:

The temperature of the case should be measured using a thermocouple placed on the case at the temperature reference point (see Note 3). The thermal mass connected to the case is normally large enough so that it will not significantly respond to heat surges generated in the diode as a result of pulsed operation once steady-state conditions are achieved. Using the measured value of T_C , the junction temperature may be determined by:


$$T_j = T_C + \Delta T_{JC}$$

where ΔT_{JC} is the increase in junction temperature above the case temperature. It may be determined by:

$$\Delta T_{JC} = P_{pk} \cdot R_{\theta JC} [D + (1 - D) \cdot r(t_1 + t_p) + r(t_p) - r(t_1)]$$


where $r(t)$ = normalized value of transient thermal resistance at time, t , from Figure 3, i.e.:
 $r(t_1 + t_p)$ = normalized value of transient thermal resistance at time $t_1 + t_p$.

FIGURE 3 – THERMAL RESPONSE



SINE WAVE INPUT

FIGURE 4 – FORWARD POWER DISSIPATION



SQUARE WAVE INPUT

FIGURE 5 – FORWARD POWER DISSIPATION




FIGURE 6 – CURRENT DERATING




FIGURE 7 – CURRENT DERATING




FIGURE 8 – TYPICAL REVERSE CURRENT





FIGURE 9 – NORMALIZED REVERSE CURRENT



TYPICAL DYNAMIC CHARACTERISTICS

FIGURE 10 – FORWARD RECOVERY TIME





FIGURE 11 – JUNCTION CAPACITANCE



TYPICAL RECOVERED STORED CHARGE DATA

FIGURE 12 – $T_J = 25^\circ C$

(See Note 2)




FIGURE 13 – $T_J = 75^\circ C$




FIGURE 14 – $T_J = 100^\circ C$




FIGURE 15 – $T_J = 150^\circ C$

