


The RF Line UHF Power Transistors

... designed primarily for wideband, large-signal output and driver amplifier stages in the 600 to 1000 MHz frequency range.

- Designed for Class C, Common Base Power Amplifiers
- Specified 28 Volt, 1000 MHz Characteristics:
 - Output Power — 3 to 18 Watts
 - Power Gain — 7.8 dB Min, Common Base
 - Collector Efficiency — 50 to 55%
- Built-In Matching Network for Broadband Operation
- Gold Metallization for Improved Reliability
- Diffused Ballast Resistors
- Hermetic Package for Military/Space Applications

MRA0610H Series

7.8 dB
600-1000 MHz
3 TO 18 WATTS
BROADBAND
UHF POWER
TRANSISTORS



CASE 393-01, STYLE 1
 (HLP-11)

MAXIMUM RATINGS

Rating	Symbol	-3H	-9H	-18H	Unit
Collector-Base Voltage	V_{CES}		50		Vdc
Emitter-Base Voltage	V_{EBO}		3.5		Vdc
Collector Current — Continuous	I_C	0.5	1.5	2.5	Adc
Operating Junction Temperature	T_J	200			°C
Storage Temperature Range	T_{stg}	-65 to +200			°C

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max			Unit
Thermal Resistance, RF, Junction to Case	$R_{\theta JC}$	15	6	4	°C/W

ELECTRICAL CHARACTERISTICS

Characteristic	Symbol	Min	Typ	Max	Unit
----------------	--------	-----	-----	-----	------

OFF CHARACTERISTICS

Collector-Emitter Breakdown Voltage $(I_C = 20 \text{ mA}, V_{BE} = 0)$ $(I_C = 60 \text{ mA}, V_{BE} = 0)$ $(I_C = 100 \text{ mA}, V_{BE} = 0)$	MRA0610- 3H - 9H -18H	$V(BR)_{CES}$	50 50 50	— — —	— — —	Vdc
Emitter-Base Breakdown Voltage $(I_E = 0.25 \text{ mA}, I_C = 0)$ $(I_E = 0.75 \text{ mA}, I_C = 0)$ $(I_E = 1.25 \text{ mA}, I_C = 0)$	MRA0610- 3H - 9H -18H	$V(BR)_{EBO}$	3.5 3.5 3.5	— — —	— — —	Vdc
Collector Cutoff Current $(V_{CB} = 28 \text{ V}, I_E = 0)$	MRA0610- 3H - 9H -18H	I_{CBO}	— — —	— — —	0.5 1.5 2.5	mAdc

ON CHARACTERISTICS

DC Current Gain $(I_C = 100 \text{ mA}, V_{CE} = 5 \text{ V})$ $(I_C = 300 \text{ mA}, V_{CE} = 5 \text{ V})$ $(I_C = 500 \text{ mA}, V_{CE} = 5 \text{ V})$	MRA0610- 3H - 9H -18H	h_{FE}	10 10 10	— — —	100 100 100	—
---	-----------------------------	----------	----------------	-------------	-------------------	---

(continued)

Characteristic	Symbol	Min	Typ	Max	Unit	
DYNAMIC CHARACTERISTICS						
Output Capacitance ($V_{CB} = 28\text{ V}$, $I_E = 0$, $f = 1\text{ MHz}$)	MRA0610- 3H - 9H -18H	C_{ob}	— — —	— — —	4.5 10 14	pF
FUNCTIONAL TESTS						
Common-Base Amplifier Power Gain ($V_{CE} = 28\text{ V}$, $P_{out} = 3\text{ W}$, $f = 600\text{ MHz}$ and 1 GHz)	MRA0610- 3H - 9H -18H	G_{PB}	7.8 7.8 7.8	— — —	— — —	dB
Collector Efficiency ($V_{CE} = 28\text{ V}$, $P_{out} = 3\text{ W}$, $f = 600\text{ MHz}$ and 1 GHz)	MRA0610- 3H - 9H -18H	η_c	50 55 55	— — —	— — —	%

TYPICAL CHARACTERISTICS

www.DataSheet4U.com


Note: Divide by t_C^2 to obtain metal lifetime in hours.

Figure 1. MTTF Factor versus Junction Temperature