

Description:

UNC 2-56 thread, 80,000psi tensile strength, length: 13/64in., head width: 5/64in., thread length: 9/64in., MS16995 series screw

MS16995-1 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Screw, Cap, Socket Head
NSN:	5305-00-068-5409
NIIN:	000685409
FSC:	Screws / 5305
Associated NSN(s):	• 5305-00-068-5277
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

MS16995-1 Specifications

Fastener Length:	0.172 Inches Minimum And 0.204 Inches Maximum
Hardness Rating:	80.0 Rockwell B Minimum Overall
Head Diameter:	0.134 Inches Minimum And 0.140 Inches Maximum
Head Height:	0.083 Inches Minimum And 0.086 Inches Maximum
Head Style:	Flat Chamfer
Material:	Steel Corrosion Resisting Overall
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Minimum Yield Strength:	30000 Pounds Per Square Inch
Nominal Thread Diameter:	0.086 Inches
Internal Drive Style:	Hexagon
Material Document And Classification:	66 Fed Std Single Material Response Overall
Width Across Flats:	0.078 Inches Minimum And 0.079 Inches Maximum
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Surface Treatment:	Passivate Overall
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.116 Inches Minimum And 0.148 Inches Maximum
Thread Quantity Per Inch:	56
Thread Series Designator:	Unc

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket-head-cap-screws/MS16995-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.