

# **P/N MS21052-3K**

# **Description**

Thread Size: 13/64", Nut Length: 61/64", Nut Height: 1/4", MS21052 series nut

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

### **Additional Information**

SKU / Model: MS210523K

Minimum Qty (MOQ): 10

NSN: 5310-00-775-2518

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21052-3K Specifications

**Surface Treatment Document And Classification:** 

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.194 Inches Minimum Nut
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.950 Inches Maximum
Nut Height:	0.250 Inches Maximum
Plate Thickness:	0.047 Inches Maximum
Plate Width:	0.308 Inches Minimum And 0.328 Inches Maximum
Nut Counterbore Depth:	0.062 Inches Minimum Nut
Nut Mounting Provision:	Countersunk Holes
Mounting Provision Location:	Opposite Nut Projection Side
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.339 Inches Minimum And 0.349 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.310 Inches Minimum And 0.314 Inches Maximum
Temp Rating:	800.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.190 Inches
Mounting Hole Countersink Angle:	98.0 Degrees Minimum And 102.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Precious Material And Location:	All Surfaces Silver
Precious Material:	Silver
Surface Treatment:	Silver Overall

Ams 2410 Assn Std Single Treatment Response Overall

# How to Order Order this self-locking nutplate from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21052-3K">https://military-fasteners.com/nuts/self\_locking+nutplates/MS21052-3K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21052-3K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21052-3K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21052-3K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21052-3K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21052-3K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21052-3K</a> and selecting the your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21052-3K</a> and selecting the your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21052-3K</a> and you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplate