

MS21075L08N SELF-LOCKING NUTPLATE SPEC

Description:

Thread: 8-32, two lug, floating, reduced rivet spacing, low height, cadmium plated carbon steel, dry film lube, without eyelets, MS21075 series nut

MS21075L08N Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Nut, Self-locking, Plate
NSN:	5310-01-345-1813
NIIN:	013451813
FSC:	Nuts and Washers / 5310
Schedule B:	7318.16.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

MS21075L08N Specifications

Center To Center Distance Between Mounting Holes Along Length:	0.463 Inches Minimum And 0.473 Inches Maximum
Distance From Aperture Center To Mounting Hole Center:	0.229 Inches Minimum And 0.239 Inches Maximum
Features Provided:	Floating Nut
Hardness Rating:	49.0 Rockwell C Maximum
Material:	Steel Overall
Mounting Hole Arrangement Style:	2 Holes
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nominal Thread Size:	0.164 Inches
Nut Length:	0.707 Inches Maximum
Nut Height:	0.250 Inches Maximum
Nut Mounting Provision:	Straight Holes
Nut Style:	Plate
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Plate Thickness:	0.140 Inches Maximum
Plate Width:	0.290 Inches Minimum And 0.367 Inches Maximum
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Class:	3b
Thread Direction:	Right-hand
Thread Quantity Per Inch:	32
Thread Series:	Unjc

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking-nutplates/MS21075L08N and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.