

SEVEN SEGMENT NUMERIC DISPLAY

High Performance GaP, GaAsP Dice

0.3 inch Character Height

High Contrast

Wide Viewing Angle

Common Anode - MS231A, MG231A, MY231A, MO231A

Common Cathode - MS231C, MG231C, MY231C, MO231C

ABSOLUTE MAXIMUM RATINGS

ABSOLUTE MAXIMUM RATINGS	MG231			UNIT
	MS231	MY231	MO231	
Power Dissipation / Segment	40	60	75	mW
Peak Forward Current / Segment	60	80	100	mA
Continuous Forward Current / Segment	15	20	25	mA
Reverse Voltage / Segment	5	5	5	V
Operating Temperature Range	-25 to +85			°C
Storage Temperature Range	-25 to +85			°C
Lead Soldering Temperature (1/16" from body, 5 sec.)	260			°C
* Note : Pulse Width = 1mS, Duty Ratio = 1/10.				

ELECTRO-OPTICAL CHARACTERISTICS (Ta=25°C)

PARAMETER		SYMBOL	MS231	MG231	MY231	MO231	UNIT	CONDITIONS
Forward Voltage	MAX	VF	3.0	3.0	3.0	3.0	V	IF=20mA
Luminous Intensity	MIN	IV	320	1200	800	960	μcd	IF=10mA
	TYP		450	2100	1200	1600	μcd	IF=10mA
Segment to Segment	MAX		2:1	2:1	2:1	2:1		IF=20mA
Luminous Intensity Ratio								
Reverse Current Any Bar	MAX	IR	100	100	100	100	μA	VR=5V
Peak Wavelength	TYP	λp	700	565	585	630	nm	IF=20mA
Spectral Line Half Width	TYP	Δλ	100	30	35	35	nm	IF=20mA




MICRO ELECTRONICS LTD.

38, Hung To Road, Microtron Building, Kwun Tong, Kowloon, Hong Kong.

Kwun Tong P.O. Box 69477 Hong Kong. Fax No. 2341 0321 Telex: 43510 Micro Hx. Tel: 2343 0181-5

May-97

MECHANICAL OUTLINE:



CIRCUIT DIAGRAM:

