

Description:

Fastener Length: 3/8", Thread: 4-40, Head Width: ", Thread Length: 3/8"

MS24667-2 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Screw, Cap, Socket Head
NSN:	5305-00-050-4271
NIIN:	000504271
FSC:	Screws / 5305
Associated NSN(s):	• 5305-00-682-5759
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

MS24667-2 Specifications

Countersink Angle:	80.0 Degrees Minimum And 84.0 Degrees Maximum
Fastener Length:	0.375 Inches Nominal
Hardness Rating:	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Head Diameter:	0.218 Inches Minimum And 0.255 Inches Maximum
Head Style:	Flat Countersunk
Material:	Steel Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Diameter:	0.112 Inches
Internal Drive Style:	Hexagon
Material Document And Classification:	66 Fed Std Single Material Response Overall
Width Across Flats:	0.062 Inches Nominal
Surface Treatment Document And Classification:	Qq-p-416,type 2 Class 3 Fed Spec Single Treatment Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.325 Inches Minimum And 0.375 Inches Maximum
Thread Quantity Per Inch:	40
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket-head-cap-screws/MS24667-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.