

Description:

Length: 5/8", thread: 10-32, socket head screw - corrosion resistant steel - drilled head

MS24673-3 Manufacturer certs (CofC) are provided free on all orders

Order this part online



Additional Information

Gov. Issued Name:	Socket Head Cap Screw
NSN:	5305-00-988-5308
NIIN:	009885308
FSC:	Screws / 5305
Associated NSN(s):	• 5305-00-726-5578
Schedule B:	7318.15.2000, Bolts and bolts and their nuts or washers exported in the same shipment
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

MS24673-3 Specifications

Fastener Length:	0.625 Inches Nominal
Hardness Rating:	80.0 Rockwell B Minimum Overall
Head Diameter:	0.303 Inches Minimum And 0.312 Inches Maximum
Head Height:	0.185 Inches Minimum And 0.195 Inches Maximum
Head Style:	Flat Chamfer
Hole Configuration Style:	Round Internal Hexagon
Hole Diameter:	0.050 Inches Nominal
Hole Quantity:	6
Hole Type:	Drilled
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Minimum Yield Strength:	30000 Pounds Per Square Inch
Nominal Thread Diameter:	0.190 Inches
Internal Drive Style:	Hexagon
Material Document And Classification:	66 Fed Std All Material Responses Overall
Width Across Flats:	0.156 Inches Minimum And 0.159 Inches Maximum
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Surface Treatment:	Passivate Overall
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.579 Inches Minimum
Thread Quantity Per Inch:	32
Thread Series Designator:	Unf

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket-head-cap-screws/MS24673-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.