


Part Number: MS35 20010



### Electrical Specifications:

Resistance @ 25°C	20.0 $\Omega$
Max Steady State Current Up to 65°C	10.0 A
Max Recommended Energy Rating (Joules)	500.0 J
Rhot @ 100% Steady State Current	0.100 $\Omega$
Rhot @ 75% Steady State Current	0.320 $\Omega$
Rhot @ 50% Steady State Current	0.480 $\Omega$
Rhot @ 25% Steady State Current	1.250 $\Omega$
Max Capacitance @ Max Voltage	1000 $\mu$ F
Max Recommended Voltage	680 V
Material Type	"M"

### Mechanical Specifications:

D	35.0 $\pm$ 2.5 mm
T	10.0 $\pm$ 2.0 mm
Lead Diameter	2.5 $\pm$ 0.1 mm
S	19.0 $\pm$ 3.0 mm
L	39.0 $\pm$ 4.0 mm
Straight Leads Coating Run Down	9.0 mm Max
B	25.0 $\pm$ 2.5 mm
C	7.50 $\pm$ 1.0 mm

Revision Date: March 19, 2003

**Ametherm, Inc.** 3111 N. Deer Run Road #4 Carson City, NV 89701  
 Telephone: (800) 808-2434 (775) 884-2434 Fax: (775) 884-0670

[www.ametherm.com](http://www.ametherm.com)