

Description:

Length: 7/8", thread: 6-32, pan head, black brass, coarse thread

MS35214-30 Manufacturer certs (CofC) are provided free on all orders

Order this part online



Additional Information

Gov. Issued Name:	Screw, Machine
NSN:	5305-00-059-8255
NIIN:	000598255
FSC:	Screws / 5305
Associated NSN(s):	<ul style="list-style-type: none">• 5305-00-013-3228• 5305-00-272-4680• 5305-00-286-1952• 5305-00-531-1430• 5305-00-616-2459• 5305-00-639-6336
Schedule B:	7415.33.8550, Other copper screws (not for wood) bolts and nuts
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper
Manufacturer Country:	United States

See page 2 for technical characteristics

MS35214-30 Specifications

Fastener Length:	0.875 Inches Nominal
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Head Style:	Pan
Minimum Tensile Strength:	57000 Pounds Per Square Inch
Nominal Thread Diameter:	0.138 Inches
Internal Drive Style:	Cross Recess Type 1
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.813 Inches Minimum And 0.875 Inches Maximum
Thread Quantity Per Inch:	32
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine-screws/MS35214-30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.