



AVIAQUIP

MS51844 Oval Splices (Nicopress Sleeves) Sleeve, Swaging, Wire Rope.



MS51844	NICOPRESS	LOOS & CO	PLATING	CABLE SIZE	A	B	C
-22	28-1-C	SL2-2P	ZINC	1/16	.270	.440	.180
-23	28-2-G	SL2-3P		3/32	.380		.240
-24	28-3-M	SL2-4P		1/8	.512	.750	.340
-25	28-4-P	SL2-5P		5/32	.600		.370
-26	28-6-X	SL2-6P		3/16	.710	1.00	.450
-42	18-1-C	SL2-2		NONE	1/16	.270	.440
-43	18-2-G	SL2-3	3/32		.380	.240	
-44	18-3-M	SL2-4	1/8		.512	.750	.340
-45	18-4-P	SL2-5	5/32		.600		.370
-46	18-6-X	SL2-6	3/16		.710	1.00	.450
-82	428-2-VC	SL2-2TP	TIN		1/16	.270	.440
-83	428-3-VG	SL2-3TP		3/32	.380	.240	
-84	428-4-VM	SL2-4TP		1/8	.512	.750	.340
-85	428-5-VP	SL2-5TP		5/32	.600		.370
-86	428-6-VX	SL2-6TP		3/16	.710	1.00	.450

MS20995 SAFETY LOCK WIRE



MATERIAL SELECTION:

MS20995 C (diameter) 304 Stainless Steel Not Temperature Rated
 MS20995 N (diameter) Inconel For use at temperature 700°F. and above
 AVIAQUIP stocks MS20995 C20, C25, C32, C41, C51, CU20, N20, N25, N40, N51, N32
 NC20, NC32 & NC40

Diameter Selection Replace (xx) with material code

MS20995(XX)25	MS20995(XX)32	MS20995(XX)41
.025" DIA. For small screws with hole diameter of less than .045"	.032" DIA. General Purpose #10 to 3/8" diameter bolts Secondary Turnbuckles	.041" DIA. Primary Turnbuckles Propeller Bolts Large Fasteners

Product information and part numbers shown on these pages are not guaranteed correct by AVIAQUIP PTY. LTD and are subject to change without notice.