


## Low-Voltage, High-Precision, Push-Pull Output Comparator


### PRODUCT DESCRIPTION

The MS8923/8923S is a differential input, high-speed and low power dissipation comparator with complementary TTL outputs. Its propagation delay is about 10ns and its common-mode input range includes the negative rail. The MS8923/8923S output can remain stable output in the linear region. The single power supply is +5.0V and the dual power supply is  $\pm 5V$ .

The MS8923 is available in SOP8 package. The MS8923S is available in SOT23-5 package.



SOP8



SOT23-5

### FEATURES

- Fast Propagation Delay: 10ns
- Single Power Supply +5V or Dual Power Supply  $\pm 5V$
- Input Voltage Range below the Negative Rail
- Low Power Dissipation: 6mA
- No Requirement for the Minimum Input Signal Changing Rate
- Stable in the Linear Region
- Input Offset Voltage: 0.8mV
- Operating Temperature:  $-40^{\circ}C \sim 120^{\circ}C$


### APPLICATIONS

- Handheld and Battery-powered Systems
- Scanner and Set Top Box
- High-speed Differential Line Receiver
- Window Comparator
- Zero-crossing Monitor
- High-speed Sampling Circuit
- V/F Converter

### PRODUCT SPECIFICATION

| Part Number | Package | Marking |
|-------------|---------|---------|
| MS8923      | SOP8    | MS8923  |
| MS8923S     | SOT23-5 | 8923S   |

## PIN CONFIGURATION



## PIN DESCRIPTION

| Pin            | Name | Type | Description                                                                                                                                               |
|----------------|------|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>MS8923</b>  |      |      |                                                                                                                                                           |
| 1              | V+   | -    | Positive Power Supply                                                                                                                                     |
| 2              | IN+  | I    | Positive Input                                                                                                                                            |
| 3              | IN-  | I    | Negative Input                                                                                                                                            |
| 4              | V-   | -    | Negative Power Supply                                                                                                                                     |
| 5              | LE   | I    | Latch Enable Pin. When LE is in high level or floating, Q and QN outputs are latched; When LE is in low level, the outputs of Q and QN change with input. |
| 6              | GND  | -    | Logic Ground                                                                                                                                              |
| 7              | Q    | O    | Positive Output of Comparator                                                                                                                             |
| 8              | QN   | O    | Negative Output of Comparator                                                                                                                             |
| <b>MS8923S</b> |      |      |                                                                                                                                                           |
| 1              | Q    | O    | Positive Output of Comparator                                                                                                                             |
| 2              | V-   | -    | Negative Power Supply                                                                                                                                     |
| 3              | IN+  | I    | Positive Input                                                                                                                                            |
| 4              | IN-  | I    | Negative Input                                                                                                                                            |
| 5              | V+   | -    | Positive Power Supply                                                                                                                                     |

## ABSOLUTE MAXIMUM RATINGS

Any exceeding absolute maximum rating application causes permanent damage to device. Because long-time absolute operation state affects device reliability. Absolute ratings just conclude from a series of extreme tests. It doesn't represent chip can operate normally in these extreme conditions.

| Parameter                               | Symbol           | Range        | Unit |
|-----------------------------------------|------------------|--------------|------|
| Positive Power Supply Range             | V+               | +7           | V    |
| Negative Power Supply Range             | V-               | -7           | V    |
| Power Supply Range                      | (V+)-(V-)        | +13          | V    |
| Differential Input Voltage Range        | VID              | +15          | V    |
| Input Voltage Range<br>(Referred to V-) |                  | -0.3 ~ +14   | V    |
| Maximum Voltage on Latch Pin            | V(LE)            | Power Supply | V    |
| Maximum Junction Temperature            |                  | +150         | °C   |
| Storage Temperature                     | T <sub>stg</sub> | -60 ~ 150    | °C   |
| Lead Temperature(10s)                   |                  | 260          | °C   |
| ESD Voltage(HBM)                        |                  | 2000         | V    |
| ESD Voltage(MM)                         |                  | 200          | V    |


# ELECTRICAL CHARACTERISTICS

Unless otherwise noted,  $T_A = T_{MIN} \sim T_{MAX}$ ,  $V_Q = +1.4V$ ,  $V_+ = +5V$ ,  $V_- = -5V$ ,  $V_{LE} = 0V$ .

| Parameter                            |            | Symbol          | Condition                                                | Min  | Typ  | Max  | Unit             |
|--------------------------------------|------------|-----------------|----------------------------------------------------------|------|------|------|------------------|
| Input Offset Voltage                 |            | $V_{OS}$        | $R_S \leq 100\Omega$ , $T_A = +25^\circ C$               |      | 0.1  | 2    | mV               |
|                                      |            |                 | $R_S \leq 100\Omega$ , $T_A = T_{MIN} \sim T_{MAX}$      |      |      | 3    |                  |
| Input Offset Drift                   |            | $TCV_{OS}$      |                                                          |      | 2    |      | $\mu V/^\circ C$ |
| Input Bias Current                   |            | $I_B$           | $T_A = +25^\circ C$                                      |      | 2    | 5    | $\mu A$          |
|                                      |            |                 | C, E Temperature Ranges                                  |      |      | 8    |                  |
| Input Offset Current                 |            | $I_{OS}$        | $T_A = +25^\circ C$                                      |      | 0.3  | 0.5  | $\mu A$          |
|                                      |            |                 | $T_A = T_{MIN} \sim T_{MAX}$                             |      |      | 1    |                  |
| Common-mode Rejection Ratio          |            | CMRR            | $-4.2V < V_{CM} < +3.5V$                                 | 80   | 110  |      | dB               |
| Input Common-mode Voltage Range      |            | CMVR            | C, E Temperature Ranges                                  | -4.2 |      | +3.5 | V                |
|                                      |            |                 | Single Power Supply: +5V, C, E Temperature Ranges        | 0.8  |      | +3.5 |                  |
| Power Supply Rejection Ratio         |            | PSRR            | Positive Power Supply: $4.5V \leq V_+ \leq 5.5V$         | 60   | 85   |      | dB               |
|                                      |            |                 | Negative Power Supply: $-4.5V \leq V_- \leq -5.5V$       | 80   | 100  |      |                  |
| Small Signal Voltage Gain            |            | $A_V$           | $1V \leq V_Q \leq 2V$ , $T_A = +25^\circ C$              | 1500 | 3500 |      | V/V              |
| Output Voltage                       | High-level | $V_{OH}$        | $V_+ \geq 4.5V$ , $I_{OUT} = 10mA$                       | 3.0  | 3.3  |      | V                |
|                                      | Low-level  | $V_{OL}$        | $I_{SINK} = 4mA$                                         |      | 0.3  | 0.5  |                  |
| Positive Power Supply Current        |            | $I_+$           | C, E Temperature Ranges                                  |      | 6.7  | 10   | mA               |
| Negative Power Supply Current        |            | $I_-$           |                                                          |      | 1    | 2    | mA               |
| High-level Input on Latch pin        |            | $V_{IH}$        |                                                          | 2.0  |      |      | V                |
| Low-level Input on Latch pin         |            | $V_{IL}$        |                                                          |      |      | 0.8  | V                |
| Input Current on Latch pin           |            | $I_{IL}$        | $V_{LE} = 0V$                                            |      | -3   | -20  | $\mu A$          |
| Propagation Delay                    | $t_{PD+}$  |                 | $\Delta V_{IN} = 100mV$ , $V_{OD} = 5mV$ , $25^\circ C$  |      | 5.5  | 8    | ns               |
|                                      | $t_{PD-}$  |                 | $\Delta V_{IN} = 100mV$ , $V_{OD} = 20mV$ , $25^\circ C$ |      | 5.5  | 8    |                  |
| Propagation Delay Skew               |            | $\Delta t_{PD}$ |                                                          |      | 1    | 3    | ns               |
| Latch Setup Time <sup>1</sup>        |            | $t_{SU}$        |                                                          | 2    | 0    |      | ns               |
| Latch Hold Time <sup>1</sup>         |            | $t_H$           |                                                          | 5    | 2    |      | ns               |
| Latch Propagation Delay <sup>2</sup> |            | $t_{LPD}$       |                                                          |      | 7    |      | ns               |

Note:

1. Latch setup time is the stable time when input signal is prior to latch signal. Latch hold time is the time when input signal remains unchanged after latch time.
2. Latch propagation delay time is the time from the change of latch signal to the output response.



## TYPICAL APPLICATION DIAGRAM

### Simple Comparator

A simple comparator is used to convert the analog input signal to digital output signal. The comparator compares an input voltage ( $V_{IN}$ ) on the non-inverting pin with the reference voltage ( $V_{REF}$ ) on the inverting pin. If  $V_{IN}$  is less than  $V_{REF}$ , the output voltage is low. If  $V_{IN}$  is greater than  $V_{REF}$ , the output voltage is high.




Figure 1. Simple Comparator

### Hysteresis Effect

If the differential input of the simple comparator is close to the offset voltage, the comparator will oscillate or produce noisy oscillation. It usually occurs when one input voltage is equal or very close to the other input voltage. Hysteresis can address this problem. Hysteresis can produce two comparison thresholds (one for the rising process and the other for the falling process). Hysteresis value is the difference between two comparison thresholds. When both inputs are very close, hysteresis would cause one input voltage to exceed the other voltage quickly. Thus, the input voltage is moved out of the region in which oscillation may occur.

As shown in Figure 2, hysteresis can be formed by connecting two resistors to the non-inverting pin, which is the positive feedback. When  $V_{IN}$  rises up to  $V_{IN1}$ , the output would change from low to high.  $V_{IN1}$  can be calculated from the following formula:

$$V_{IN1} = V_{REF} \times \frac{R_1 + R_2}{R_2}$$

When  $V_{IN}$  falls to  $V_{IN2}$ , the output would change from high to low.  $V_{IN2}$  can be calculated from the following formula:

$$V_{IN2} = V_{REF} \times \frac{R_1 + R_2}{R_2} - (V+) \times \frac{R_1}{R_2}$$

The hysteresis value is the difference between  $V_{IN1}$  and  $V_{IN2}$ :

$$\Delta V_{IN} = V_{IN1} - V_{IN2} = V_{CC} \times \frac{R_1}{R_2}$$




Figure 2. Non-inverting Comparator Circuit

### Input


Input bias current of the MS8923/8923S is near zero, which allows the use of high-impedance circuit without considering impedance match. This also allows the use of small-capacitor in R-C type timing circuit and reduces the use of the capacitor and the space of circuit board.

### Board Layout and Bypassing

Although the MS8923/8923S is stable and has an anti-interference ability, it is important to use appropriate bypassing capacitors and ground pickups. The 0.1 $\mu$ F ceramic capacitor can provide clean power and the shortest signal line can reduce stray capacitance.


# PACKAGE OUTLINE DIMENSIONS

## SOP8



| Symbol | Dimensions in Millimeters |       | Dimensions in Inches |       |
|--------|---------------------------|-------|----------------------|-------|
|        | Min                       | Max   | Min                  | Max   |
| A      | 1.350                     | 1.750 | 0.053                | 0.069 |
| A1     | 0.100                     | 0.225 | 0.004                | 0.010 |
| A2     | 1.350                     | 1.550 | 0.053                | 0.061 |
| b      | 0.330                     | 0.510 | 0.013                | 0.020 |
| c      | 0.170                     | 0.250 | 0.006                | 0.010 |
| D      | 4.700                     | 5.100 | 0.185                | 0.200 |
| E      | 3.800                     | 4.000 | 0.150                | 0.157 |
| E1     | 5.800                     | 6.200 | 0.228                | 0.244 |
| e      | 1.27(BSC)                 |       | 0.050(BSC)           |       |
| L      | 0.400                     | 1.270 | 0.016                | 0.050 |
| θ      | 0°                        | 8°    | 0°                   | 8°    |


## SOT23-5



| Symbol | Dimensions in Millimeters |       | Dimensions in Inches |       |
|--------|---------------------------|-------|----------------------|-------|
|        | Min                       | Max   | Min                  | Max   |
| A      | 1.050                     | 1.250 | 0.041                | 0.049 |
| A1     | 0.000                     | 0.100 | 0.000                | 0.004 |
| A2     | 1.050                     | 1.150 | 0.041                | 0.045 |
| b      | 0.300                     | 0.500 | 0.012                | 0.020 |
| c      | 0.100                     | 0.200 | 0.004                | 0.008 |
| D      | 2.820                     | 3.020 | 0.111                | 0.119 |
| E      | 1.500                     | 1.700 | 0.059                | 0.067 |
| E1     | 2.650                     | 2.950 | 0.104                | 0.116 |
| e      | 0.950(BSC)                |       | 0.037(BSC)           |       |
| e1     | 1.900(BSC)                |       | 0.075(BSC)           |       |
| L      | 0.300                     | 0.600 | 0.012                | 0.024 |
| θ      | 0°                        | 8°    | 0°                   | 8°    |

## MARKING and PACKAGING SPECIFICATIONS

### 1. Marking Drawing Description



Product Name: MS8923, 8923S

Product Code: XXXXX, XXXXXXX

### 2. Marking Drawing Demand

Laser printing, contents in the middle, font type Arial.

### 3. Packaging Specifications

| Device  | Package | Piece/Reel | Reel/Box | Piece /Box | Box/Carton | Piece/Carton |
|---------|---------|------------|----------|------------|------------|--------------|
| MS8923  | SOP8    | 2500       | 1        | 2500       | 8          | 20000        |
| MS8923S | SOT23-5 | 3000       | 10       | 30000      | 4          | 120000       |

**STATEMENT**

- All Revision Rights of Datasheets Reserved for Ruimeng. Don't release additional notice.  
Customer should get latest version information and verify the integrity before placing order.
- When using Ruimeng products to design and produce, purchaser has the responsibility to observe safety standard and adopt corresponding precautions, in order to avoid personal injury and property loss caused by potential failure risk.
- The process of improving product is endless. And our company would sincerely provide more excellent product for customer.

**MOS CIRCUIT OPERATION PRECAUTIONS**

Static electricity can be generated in many places. The following precautions can be taken to effectively prevent the damage of MOS circuit caused by electrostatic discharge:

1. The operator shall ground through the anti-static wristband.
2. The equipment shell must be grounded.
3. The tools used in the assembly process must be grounded.
4. Must use conductor packaging or anti-static materials packaging or transportation.



+86-571-89966911



Rm701, No.9 Building, No. 1 WeiYe Road, Puyan Street, Binjiang District, Hangzhou, Zhejiang



[http:// www.relmon.com](http://www.relmon.com)