

# MSRB860-1

## Product Preview

### **SWITCHMODE™** **Soft Recovery Power** **Rectifier** **D<sup>2</sup>PAK-SL Straight Lead**



**ON Semiconductor®**

<http://onsemi.com>

Designed for use as free wheeling diodes in variable speed motor control applications and other average frequency switching power supplies. These state-of-the-art devices have the following features:

- Soft Recovery with Guaranteed Low Reverse Recovery Charge ( $Q_{RR}$ ) and Peak Reverse Recovery Current ( $I_{RRM}$ )
- 150°C Operating Junction Temperature
- Epoxy meets UL94,  $V_0 @ 1/8"$
- Low Forward Voltage
- Low Leakage Current
- High Temperature Glass Passivated Junction

#### **Mechanical Characteristics:**

- Case: Molded Epoxy
- Weight: 1.9 Grams (approximately)
- Finish: All External Surfaces Corrosion Resistant and Terminal Leads Readily Solderable
- Lead Temperature for Soldering Purposes: 260°C Max. for 10 Seconds
- Shipped in 50 Units per Plastic Tube
- Marking: MSRB860

**SOFT RECOVERY**  
**POWER RECTIFIER**  
**8.0 AMPERES, 600 VOLTS**



**CASE 418C-01, Style 2**  
**D<sup>2</sup>PAK-SL**

This document contains information on a product under development. Motorola reserves the right to change or discontinue this product without notice.

## MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	$V_{RRM}$ $V_{RWM}$ $V_R$	600	V
Average Rectified Forward Current (At Rated $V_R$ , $T_C = 125^\circ\text{C}$ )	$I_O$	8.0	A
Peak Repetitive Forward Current (At Rated $V_R$ , Square Wave, 20 kHz, $T_C = 125^\circ\text{C}$ )	$I_{FRM}$	16	A
Non-Repetitive Peak Surge Current (Surge applied at rated load conditions, halfwave, single phase, 60 Hz)	$I_{FSM}$	100	A
Storage / Operating Case Temperature	$T_{stg}, T_C$	- 65 to 150	$^\circ\text{C}$
Operating Junction Temperature	$T_J$	- 65 to 150	$^\circ\text{C}$

## THERMAL CHARACTERISTICS

Thermal Resistance — Junction-to-Case	$R_{\theta JC}$	1.6	$^\circ\text{C}/\text{W}$
Thermal Resistance — Junction-to-Ambient	$R_{\theta JA}$	72.8	$^\circ\text{C}/\text{W}$

## ELECTRICAL CHARACTERISTICS

Maximum Instantaneous Forward Voltage (1) ( $I_F = 8.0\text{ A}$ )	$V_F$	$T_J = 25^\circ\text{C}$	$T_J = 150^\circ\text{C}$	V
<i>Typical</i>		1.7 1.4	1.3 1.1	
Maximum Instantaneous Reverse Current ( $V_R = 600\text{ V}$ )	$I_R$	$T_J = 25^\circ\text{C}$	$T_J = 150^\circ\text{C}$	$\mu\text{A}$
<i>Typical</i>		10 2.0	1000 80	
Maximum Reverse Recovery Time (2) ( $V_R = 400\text{ V}$ , $I_F = 8.0\text{ A}$ , $di/dt = 200\text{ A}/\mu\text{s}$ )	$t_{rr}$	$T_J = 25^\circ\text{C}$	$T_J = 125^\circ\text{C}$	ns
<i>Typical</i>		120 95	190 125	
Typical Recovery Softness Factor ( $V_R = 400\text{ V}$ , $I_F = 8.0\text{ A}$ , $di/dt = 200\text{ A}/\mu\text{s}$ )	$s = t_b/t_a$	2.5	3.0	
Typical Peak Reverse Recovery Current ( $V_R = 400\text{ V}$ , $I_F = 8.0\text{ A}$ , $di/dt = 200\text{ A}/\mu\text{s}$ )	$I_{RRM}$	5.8	8.3	A
Typical Reverse Recovery Charge ( $V_R = 400\text{ V}$ , $I_F = 8.0\text{ A}$ , $di/dt = 200\text{ A}/\mu\text{s}$ )	$Q_{RR}$	350	700	nC

(1) Pulse Test: Pulse Width  $\leq 380\text{ }\mu\text{s}$ , Duty Cycle  $\leq 2\%$ (2)  $T_{RR}$  measured projecting from 25% of  $I_{RRM}$  to zero current

Switchmode is a trademark of Motorola, Inc.

## TYPICAL ELECTRICAL CHARACTERISTICS




Figure 1. Typical Forward Voltage




Figure 2. Typical Reverse Current




Figure 3. Current Derating, Case




Figure 4. Current Derating, Ambient




Figure 5. Power Dissipation

## TYPICAL ELECTRICAL CHARACTERISTICS




Figure 6. Typical Reverse Recovery Time




Figure 7. Typical Reverse Recovery Time




Figure 8. Typical Peak Reverse Recovery Current




Figure 9. Typical Peak Reverse Recovery Current




Figure 10. Typical Reverse Recovery Charge




Figure 11. Typical Reverse Recovery Charge

# MSRB860-1




Figure 12. Typical Switching Off Losses




Figure 13. Typical Switching Off Losses





Figure 14. Thermal Response

# MSRB860-1

## PACKAGE DIMENSIONS


### CASE 418C-01 ISSUE O



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
  2. CONTROLLING DIMENSION: INCH.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.340	0.380	8.64	9.65
B	0.380	0.405	9.65	10.29
C	0.160	0.190	4.06	4.83
D	0.020	0.035	0.51	0.89
E	0.045	0.055	1.14	1.40
F	0.039 REF		1.00 REF	
G	0.100 BSC		2.54 BSC	
H	0.080	0.110	2.03	2.79
J	0.018	0.025	0.46	0.64
K	0.280	0.360	7.11	9.14
S	0.276 REF		7.00 REF	
V	0.045	0.055	1.14	1.40
W	0.423	0.462	10.75	11.75

STYLE 2:  
PIN 1. GATE  
2. DRAIN  
3. SOURCE  
4. DRAIN

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5773-3850

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>  
For additional information, please contact your local Sales Representative