


Single Phase Bridge Modules MT200 — MT800



Dim. Inches		Millimeter		
		Minimum	Maximum	Notes
A	.020	.030	.508	.762
B	.350	.370	8.89	9.40
C	.745	.760	18.92	19.30
D	.405	.420	10.29	10.67
E	.775	.795	19.68	20.19

www.DataSheet4U.com

E

Microsemi
Catalog Number

Repetitive Peak
Reverse Voltage

MT200*	200V
MT400*	400V
MT600*	600V
MT800*	800V

*Available with TO3 mounting flange
For other circuit configurations, consult factory

- Glass Passivated Die
- Glass to metal construction
- Single phase rectification
- Available to 800 Volts
- Cup electrically isolated from terminals

Electrical Characteristics

Maximum DC output current, single phase	I _O 25 Amps	Sine wave, 180° conduction
Maximum case temperature	T _C 137°C	
Maximum surge current per diode	I _{FSM} 250 Amps	8.3ms, half sine, T _J = 175°C
Max I _{2t} for fusing	I _{2t} 260 A ² s	
Max peak forward voltage per diode	V _{FM} 1.2 Volts	• I _O ; T _J = 25°C+
Max peak reverse current per diode	I _{RM} 1.0 mA	V _{RRM} , T _J = 150°C
Minimum isolation voltage	V _{ISOL} 2500 VRMS	any terminal to case

*Pulse test: Pulse width 300 μsec, Duty cycle 2%

Thermal and Mechanical Characteristics

Storage temperature range	T _{STG}	-65°C to 200°C
Operating junction temperature range	T _J	-65°C to 200°C
Maximum thermal resistance per diode	R _{θJC}	2.0°C/W Junction to Lead
Typical thermal resistance	R _{θCS}	0.2°C/W Case to sink
Weight		0.53 ounces (15.0 grams) typical

PH: 303-469-2161
FAX: 303-466-3775

Microsemi Corp.
Colorado

E-65

MT200 – MT800

Figure 1
Typical Forward Characteristics – Per Diode




Figure 3
Maximum Nonrepetitive Surge Current – Per Diode




Figure 2
Forward Current Derating – Per Diode

