

MTD8060W

Features

High Reliability in Demanding Environments
Metal Can Package

Applications

Optical Sensors
Optical Switches
Optical Detectors
Fiber Optic Communications

Maximum Ratings (Ta=25°C)

Characteristic	Symbol	Max.	Test Condition	Unit
Collector Power Dissipation	P _C	250	—	mW
Collector-Emitter Voltage	V _{CE}	30	—	V
Emitter-Collector Voltage	V _{EC}	30	—	V
Collector Current	I _C	50	—	mA
Operating Temperature	T _{opr}	-30 ~ +100	—	°C
Storage Temperature	T _{stg}	-40 ~ +125	—	°C
Junction Temperature	T _j	125	—	°C
Soldering Temperature	T _{sol}	260	for 5 sec. max	°C

Opto-Electrical Characteristics (Ta=25°C)

Characteristic	Symbol	Test Condition	Min	Typ	Max	Unit
C-E Saturation Voltage	V _{CE(sat)}	I _C =0.2mA, E _e =5mW/cm ² *	—	.20	—	μA
Light Current	I _L	V _{ce} =20V, E _e =0.5mW/cm ² *	—	1.00	—	μA
Dark Current	I _D	V _{ce} =20V, E _e =0.5mW/cm ² *	—	—	100	nA
Spectral Sensitivity	λ	—	—	400~1100	—	μA
Peak Sensitivity Wavelength	λ _p	—	—	880	—	V
Beam Angle	θ	—	—	± 55°	—	deg.
Rise Time	T _r	R _L =100, V _{ce} =5V, I _C =0.5mA	—	10.00	—	ns
Fall Time	T _f	R _L =100, V _{ce} =5V, I _C =0.5mA	—	10.00	—	ns

*Color Temperature=2870°K Standard Tungston Lamp


Company Headquarters
3 Northway Lane North
Latham, New York 12110
Toll Free: 800.984.5337
Fax: 518.785.4725



Web: www.marktechopto.com | Email: info@marktechopto.com

California Sales Office:
950 South Coast Drive, Suite 265
Costa Mesa, California 92626
Toll Free: 800.984.5337
Fax: 714.850.9314

www.DataSheet4U.com



MTD8060W Graphs

