

MTE1011P

Features



High Output Power
High Reliability
Narrow Beam Angle

Applications

Optical Switches
Bar Code Reader

Maximum Ratings (Ta=25°C)

Characteristic	Symbol	Max.	Test Condition	Unit
Forward Current	I _F	100	—	mA
Pulsed Forward Current	I _{FP}	2.00	tw=10μS, T=10mS	A
Reverse Voltage	V _R	5	—	V
Power Dissipation	P _D	170.00	—	mW
Operating Temperature	T _{opr}	-20~+85	—	°C
Storage Temperature	T _{stg}	-30 ~+100	—	°C
Junction Temperature	T _j	100	—	°C
Soldering Temperature	T _{sol}	260	for 5 sec. max	°C



Opto-Electrical Characteristics (Ta=25°C)

Characteristic	Symbol	Test Condition	Min	Typ	Max	Unit
Forward Voltage	V _F	I _F =50mA	—	1.40	1.70	V
Reverse Current	I _R	V _R =5V	—	—	100	μA
Power Output	P _O	I _F =50mA	2.00	3.50	—	mW
Half Intensity Beam Angle	θ	—	—	± 4°	—	deg.
Peak Wavelength	λ _p	I _F =50mA	—	880	—	nm
Spectral Line Half Width	Δλ	I _F =50mA	—	80	—	nm


Company Headquarters

3 Northway Lane North
Latham, New York 12110
Toll Free: 800.984.5337
Fax: 518.785.4725

West Coast Sales Office

950 South Coast Drive, Suite 265
Costa Mesa, California 92626
Toll Free: 800.984.5337

MTE1011P Graphs



Company Headquarters
 3 Northway Lane North
 Latham, New York 12110
 Toll Free: 800.984.5337
 Fax: 518.785.4725

West Coast Sales Office
 950 South Coast Drive, Suite 265
 Costa Mesa, California 92626
 Toll Free: 800.984.5337
 Fax: 714.850.9314