

MTE2050S-OH1

Features


High Output Power
Narrow Beam Angle
High Reliability

Applications

Optical Switches
Bar Code Reader

Maximum Ratings (Ta=25°C)

Characteristic	Symbol	Max.	Test Condition	Unit
Forward Current	I _F	100	—	mA
Pulsed Forward Current	I _{FP}	1.00	tw=10μs, T=10mS	A
Reverse Voltage	V _R	5	—	V
Power Dissipation	P _D	180.00	—	mW
Operating Temperature	T _{opr}	-20~+80	—	°C
Storage Temperature	T _{stg}	-30~+100	—	°C
Junction Temperature	T _j	100	—	°C
Soldering Temperature	T _{sol}	260	for 5 sec. max	°C



① Anode

② Cathode

Opto-Electrical Characteristics (Ta=25°C)

Characteristic	Symbol	Test Condition	Min	Typ	Max	Unit
Forward Voltage	V _F	I _F =50mA	—	1.45	1.80	V
Reverse Current	I _R	V _R =5V	—	—	10	μA
Power Output	P _O	I _F =50mA	—	11.00	—	mW
Half Intensity Beam Angle	θ	—	—	± 12°	—	deg.
Peak Wavelength	λ _p	I _F =50mA	—	880	—	nm
Spectral Line Half Width	Δλ	I _F =50mA	—	60	—	nm
Rise Time	T _r	I _{FP} =50mA	—	1.50	—	ns
Fall Time	T _f	I _{FP} =50mA	—	.80	—	ns
Temp Coefficient of PO	P/T	I _F =10mA	—	-.50	—	%/°C
Temp Coefficient of VF	V/T	I _F =10mA	—	-1.50	—	mV/°C
Junction Capacitance	C _j	1 MHz, V=0V	—	15	—	pF








Company Headquarters

120 Broadway
Menands, New York 12204
Toll Free: 800.984.5337
Fax: 518.432.7454

West Coast Sales Office

950 South Coast Drive, Suite 265
Costa Mesa, California 92626
Toll Free: 800.984.5337
Fax: 714.850.9314

MTE2050S-OH1 Graphs



Company Headquarters
120 Broadway
Menands, New York 12204
Toll Free: 800.984.5337
Fax: 518.432.7454

West Coast Sales Office
950 South Coast Drive, Suite 265
Costa Mesa, California 92626
Toll Free: 800.984.5337
Fax: 714.850.9314