

P-Channel Enhancement Mode Power MOSFET


MTE300P10KJ3

BV_{DSS}	-100V
I_D@V_{GS}=-10V, T_C=25°C	-6.5A
R_{DS(ON)}@V_{GS}=-10V, I_D=-5A	393mΩ (typ)


Features

- Low Gate Charge
- Simple Drive Requirement
- ESD Protected Gate
- Pb-free Lead Plating & Halogen-free Package

Equivalent Circuit




Outline



Ordering Information

Device	Package	Shipping
MTE300P10KJ3-0-T3-G	TO-252 (Pb-free lead plating & halogen-free package)	2500 pcs / Tape & Reel





Absolute Maximum Ratings (T_C=25°C, unless otherwise noted)

Parameter		Symbol	Limits	Unit
Drain-Source Voltage		V _{DS}	-100	V
Gate-Source Voltage		V _{GS}	±20	
Continuous Drain Current @T _C =25°C, V _{GS} =-10V (Note 1)		I _D	-6.5	A
Continuous Drain Current @T _C =100°C, V _{GS} =-10V (Note 1)			-4.1	
Continuous Drain Current @T _A =25°C, V _{GS} =-10V (Note 2)		I _{DSM}	-1.8	
Continuous Drain Current @T _A =70°C, V _{GS} =-10V (Note 2)			-1.4	
Pulsed Drain Current (Note 3)		I _{DM}	-26	
Avalanche Current (Note 3)		I _{AS}	-12	
Avalanche Energy @ L=1mH, I _D =-6.5A, V _{DD} =-25V (Note 2)		E _{AS}	21	mJ
Total Power Dissipation	T _C =25°C (Note 1)	P _D	31	W
	T _C =100°C (Note 1)		12	
	T _A =25°C (Note 2)	P _{DSM}	2.5	
	T _A =70°C (Note 2)		1.6	
Operating Junction and Storage Temperature Range		T _J , T _{stg}	-55~+150	°C

* 100% UIS testing in condition of V_D=-25V, L=0.1mH, V_G=-10V, I_{AS}=-12A, Rated V_{DS}=-100V

Thermal Data

Parameter	Symbol	Typical	Maximum	Unit
Thermal Resistance, Junction-to-case	R _{θJC}	3.6	4	°C/W
Thermal Resistance, Junction-to-ambient, t≤10s (Note 2)	R _{θJA}	15	18	
Thermal Resistance, Junction-to-ambient, steady state		40	50	

- Note : 1. The power dissipation P_D is based on T_{J(MAX)}=150°C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.
2. The value of R_{θJA} is measured with the device mounted on 1 in² FR-4 board with 2 oz. copper, in a still air environment with T_A=25°C. The power dissipation P_{DSM} is based on R_{θJA} and the maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.
3. Pulse width limited by junction temperature T_{J(MAX)}=150°C. Ratings are based on low frequency and low duty cycles to keep initial T_J=25°C.


**Characteristics (Tc=25°C, unless otherwise specified)**

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Static					
BV _{DSS}	-100	-	-	V	V _{GS} =0V, I _D =-250μA
V _{GS(th)}	-2	-	-4		V _{DS} =V _{GS} , I _D =-250μA
I _{GSS}	-	-	±10	μA	V _{GS} =±20V, V _{DS} =0V
I _{DSS}	-	-	-1		V _{DS} =-100V, V _{GS} =0V
	-	-	-25		V _{DS} =-80V, V _{GS} =0V, T _J =125°C
R _{DS(ON)} *1	-	393	510	mΩ	V _{GS} =-10V, I _D =-5A
G _{FS} *1	-	3.9	-	S	V _{DS} =-15V, I _D =-5A
Dynamic					
Q _g *1, 2	-	6.4	9.6	nC	I _D =-11A, V _{DS} =-80V, V _{GS} =-10V
Q _{gs} *1, 2	-	2.3	-		
Q _{gd} *1, 2	-	2.3	-		
t _{d(ON)} *1, 2	-	12	18	ns	V _{DS} =-50V, I _D =-11A, V _{GS} =-10V, R _G =25Ω
t _r *1, 2	-	22	33		
t _{d(OFF)} *1, 2	-	35	53		
t _f *1, 2	-	34.6	51.9		
C _{iss}	-	304	-	pF	V _{GS} =0V, V _{DS} =-25V, f=1MHz
C _{oss}	-	42	-		
C _{rss}	-	19	-		
R _g	-	63	-	Ω	f=1MHz
Source-Drain Diode Ratings and Characteristics					
I _S *1	-	-	-6.5	A	
I _{SM} *1	-	-	-26		
V _{SD} *1	-	-0.9	-1.2	V	I _S =-5A, V _{GS} =0V
t _{rr}	-	31	46.5	ns	I _F =-9A, dI _F /dt=100A/μs
Q _{rr}	-	44	-	nC	

Note : *1.Pulse Test : Pulse Width ≤300μs, Duty Cycle≤2%


*2.Independent of operating temperature

*3.Pulse width limited by maximum junction temperature.


Recommended soldering footprintUnit ($\frac{\text{mm}}{\text{inch}}$)

Typical Characteristics


Typical Output Characteristics




Breakdown Voltage vs Ambient Temperature




Static Drain-Source On-State resistance vs Drain Current




Reverse Drain Current vs Source-Drain Voltage



Static Drain-Source On-State Resistance vs Gate-Source Voltage




Drain-Source On-State Resistance vs Junction Temperature




Typical Characteristics (Cont.)


Capacitance vs Drain-to-Source Voltage




Threshold Voltage vs Junction Temperature




Maximum Safe Operating Area




Gate Charge Characteristics



Maximum Drain Current vs Case Temperature




Typical Transfer Characteristics






Typical Characteristics (Cont.)


Forward Transfer Admittance vs Drain Current




Single Pulse Power Rating, Junction to Case




Transient Thermal Response Curves



Reel Dimension




Carrier Tape Dimension



Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds


Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (Tsmax to Tp)	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(Ts min)	100°C	150°C
-Temperature Max(Ts max)	150°C	200°C
-Time(ts min to ts max)	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (Tl)	183°C	217°C
- Time (tL)	60-150 seconds	60-150 seconds
Peak Temperature(TP)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

TO-252 Dimension



DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.087	0.094	2.200	2.400	e	0.086	0.094	2.186	2.386
A1	0.000	0.005	0.000	0.127	e1	0.172	0.188	4.372	4.772
B	0.039	0.048	0.990	1.210	H	0.163	REF	4.140	REF
b	0.026	0.034	0.660	0.860	K	0.190	REF	4.830	REF
b1	0.026	0.034	0.660	0.860	L	0.386	0.409	9.800	10.400
C	0.018	0.023	0.460	0.580	L1	0.114	REF	2.900	REF
C1	0.018	0.023	0.460	0.580	L2	0.055	0.067	1.400	1.700
D	0.256	0.264	6.500	6.700	L3	0.024	0.039	0.600	1.000
D1	0.201	0.215	5.100	5.460	P	0.026	REF	0.650	REF
E	0.236	0.244	6.000	6.200	V	0.211	REF	5.350	REF

Notes: 1.Controlling dimension: millimeters.

2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.

3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material:

- Lead : Pure tin plated.
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0.

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.