

N-Channel Enhancement Mode Power MOSFET

MTN18N20FP

 BV_{DSS} : 200V
 $R_{DS(on)(TYP)}$: 80m Ω
 I_D : 18A


Description

The MTN18N20FP is a N-channel enhancement-mode MOSFET, providing the designer with the best combination of fast switching, ruggedized device design, low on-resistance and cost effectiveness. The TO-220FP package is universally preferred for all commercial-industrial applications


Features

- Low On Resistance
- Simple Drive Requirement
- Low Gate Charge
- Fast Switching Characteristic
- Insulating package, front/back side insulating voltage=2500V(AC)
- RoHS compliant package

Symbol



Outline



**Absolute Maximum Ratings** ($T_C=25^{\circ}\text{C}$)

Parameter	Symbol	Limits	Unit
Drain-Source Voltage (Note 1)	V_{DS}	200	V
Gate-Source Voltage	V_{GS}	± 30	V
Continuous Drain Current	I_D	18*	A
Continuous Drain Current @ $T_C=100^{\circ}\text{C}$	I_D	11*	A
Pulsed Drain Current @ $V_{GS}=10\text{V}$ (Note 2)	I_{DM}	72*	A
Single Pulse Avalanche Energy @ $L=2\text{mH}$, $I_D=18\text{Amps}$, $V_{DD}=50\text{V}$	E_{AS}	324	mJ
Repetitive Avalanche Energy	E_{AR}	10	
Peak Diode Recovery dv/dt (Note 3)	dv/dt	3.0	V/ns
Maximum Temperature for Soldering @ Lead at 0.063 in(1.6mm) from case for 10 seconds	T_L	300	$^{\circ}\text{C}$
Maximum Temperature for Soldering @ Package Body for 10 seconds	T_{PKG}	260	$^{\circ}\text{C}$
Total Power Dissipation ($T_C=25^{\circ}\text{C}$)	P_d	41	W
Linear Derating Factor		0.33	W/ $^{\circ}\text{C}$
Operating Junction and Storage Temperature	T_J, T_{stg}	-55~+150	$^{\circ}\text{C}$

*Drain current limited by maximum junction temperature

Note : 1. $T_J=+25^{\circ}\text{C}$ to $+150^{\circ}\text{C}$.

2. Repetitive rating; pulse width limited by maximum junction temperature.

3. $I_{SD} \leq 10\text{A}$, $dI/dt \leq 100\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, $T_J=+150^{\circ}\text{C}$.**Thermal Data**

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-case, max	$R_{th,j-c}$	3	$^{\circ}\text{C}/\text{W}$
Thermal Resistance, Junction-to-ambient, max	$R_{th,j-a}$	62.5	$^{\circ}\text{C}/\text{W}$

**Characteristics (Tj=25°C, unless otherwise specified)**

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Static					
BV _{DSS}	200	-	-	V	V _{GS} =0, I _D =250μA
ΔBV _{DSS} /ΔT _j	-	0.2	-	V/°C	Reference to 25°C, I _D =250μA
V _{GS(th)}	2.0	-	4.0	V	V _{DS} = V _{GS} , I _D =250μA
*G _{FS}	-	12	-	S	V _{DS} =20V, I _D =9A
I _{GSS}	-	-	±100	nA	V _{GS} =±30
I _{DSS}	-	-	10	μA	V _{DS} =200V, V _{GS} =0
I _{DSS}	-	-	100		V _{DS} =160V, V _{GS} =0, T _j =125°C
*R _{DS(ON)}	-	0.08	0.12	Ω	V _{GS} =10V, I _D =9A
Dynamic					
*Q _g	-	27	-	nC	V _{DD} =160V, I _D =18A, V _{GS} =10V
*Q _{gs}	-	6	-		
*Q _{gd}	-	13	-		
*t _{d(ON)}	-	20	-	ns	V _{DD} =100V, I _D =18A, V _{GS} =10V, R _G =25 Ω
*tr	-	66	-		
*t _{d(OFF)}	-	58	-		
*tf	-	48	-		
C _{iss}	-	1233	-	pF	V _{GS} =0V, V _{DS} =25V, f=1MHz
C _{oss}	-	154	-		
C _{rss}	-	53	-		
Source-Drain Diode					
*I _S	-	-	18	A	
*I _{SM}	-	-	72		
*V _{SD}	-	-	1.5	V	I _S =18A, V _{GS} =0V
*trr	-	80	-	ns	V _{GS} =0, I _F =18A, dI/dt=100A/μs
*Q _{rr}	-	240	-	nC	


*Pulse Test : Pulse Width ≤300μs, Duty Cycle≤2%

Ordering Information


Device	Package	Shipping
MTN18N20FP	TO-220FP (RoHS compliant)	50 pcs/tube, 20 tubes/box, 4 boxes / carton

Typical Characteristics


Typical Output Characteristics




Static Drain-Source On-resistance vs Ambient Temperature




Static Drain-Source On-State resistance vs Drain Current




Drain Current vs Gate-Source Voltage



Static Drain-Source On-State Resistance vs Gate-Source Voltage




Body Diode Forward Voltage Variation vs Source Current and Temperature




Typical Characteristics(Cont.)


Capacitance vs Reverse Voltage




Brekdown Voltage vs Ambient Temperature




Maximum Safe Operating Area




Gate Charge Characteristics



Maximum Drain Current vs Case Temperature




Threshold Voltage vs Junction Temperature



Typical Characteristics(Cont.)

Transient Thermal Response Curves



Test Circuit and Waveforms




Figure 17. Gate Charge Test Circuit




Figure 18. Gate Charge Waveform




Figure 19. Resistive Switching Test Circuit




Figure 20. Resistive Switching Waveforms

Test Circuit and Waveforms(Cont.)




Figure 21. Diode Reverse Recovery Test Circuit




Figure 22. Diode Reverse Recovery Waveform




Figure 23. Unclamped Inductive Switching Test Circuit





Figure 24. Unclamped Inductive Switching Waveforms

Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds


Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T_{smax} to T_p)	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(T_{smin})	100°C	150°C
-Temperature Max(T_{smax})	150°C	200°C
-Time(t_{smin} to t_{smax})	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (T_L)	183°C	217°C
- Time (t_L)	60-150 seconds	60-150 seconds
Peak Temperature(T_p)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(t_p)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

TO-220FP Dimension



*Typical

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.171	0.183	4.35	4.65	G	0.246	0.258	6.25	6.55
A1	0.051 REF		1.300 REF		H	0.138 REF		3.50 REF	
A2	0.112	0.124	2.85	3.15	H1	0.055 REF		1.40 REF	
A3	0.102	0.110	2.60	2.80	H2	0.256	0.272	6.50	6.90
b	0.020	0.030	0.50	0.75	J	0.031 REF		0.80 REF	
b1	0.031	0.041	0.80	1.05	K	0.020		0.50 REF	
b2	0.047 REF		1.20 REF		L	1.102	1.118	28.00	28.40
c	0.020	0.030	0.500	0.750	L1	0.043	0.051	1.10	1.30
D	0.396	0.404	10.06	10.26	L2	0.036	0.043	0.92	1.08
E	0.583	0.598	14.80	15.20	M	0.067 REF		1.70 REF	
e	0.100 *		2.54*		N	0.012 REF		0.30 REF	
F	0.106 REF		2.70 REF						

Notes: 1.Controlling dimension: millimeters.

2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.

3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material:

- Lead: Pure tin plated.
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0.

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.