

# MURB1620CT

Preferred Device

## SWITCHMODE™ Power Rectifier

### D<sup>2</sup>PAK Power Surface Mount Package

These state-of-the-art devices are designed for use in switching power supplies, inverters and as free wheeling diodes.

#### Features

- Package Designed for Power Surface Mount Applications
- Ultrafast 35 Nanosecond Recovery Times
- 175°C Operating Junction Temperature
- Epoxy Meets UL 94 V-0 @ 0.125 in
- High Temperature Glass Passivated Junction
- Low Leakage Specified @ 150°C Case Temperature
- Short Heat Sink Tab Manufactured – Not Sheared!
- Similar in Size to Industrial Standard TO-220 Package
- Pb-Free Packages are Available

#### Mechanical Characteristics:

- Case: Epoxy, Molded, Epoxy Meets UL 94, V-0
- Weight: 1.7Grams (Approximately)
- Finish: All External Surfaces Corrosion Resistant and Terminal Leads are Readily Solderable
- Lead and Mounting Surface Temperature for Soldering Purposes: 260°C Max. for 10 Seconds
- Device Meets MSL1 Requirements
- ESD Ratings: Machine Model, C (>400 V)  
Human Body Model, 3B (>8000 V)

#### MAXIMUM RATINGS (Per Leg)

| Rating                                                                                                         | Symbol                          | Value       | Unit |
|----------------------------------------------------------------------------------------------------------------|---------------------------------|-------------|------|
| Peak Repetitive Reverse Voltage<br>Working Peak Reverse Voltage<br>DC Blocking Voltage                         | $V_{RRM}$<br>$V_{RWM}$<br>$V_R$ | 200         | V    |
| Average Rectified Forward Current<br>(Rated $V_R$ , $T_C = 150^\circ\text{C}$ ) Total Device                   | $I_{F(AV)}$                     | 8.0<br>16   | A    |
| Peak Repetitive Forward Current (Rated $V_R$ , Square Wave, 20 kHz, $T_C = 150^\circ\text{C}$ )                | $I_{FM}$                        | 16          | A    |
| Non-Repetitive Peak Surge Current<br>(Surge Applied at Rated Load Conditions<br>Halfwave, Single Phase, 60 Hz) | $I_{FSM}$                       | 100         | A    |
| Operating Junction and Storage<br>Temperature Range                                                            | $T_J$ , $T_{stg}$               | -65 to +175 | °C   |



Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.



ON Semiconductor®

<http://onsemi.com>

### ULTRAFAST RECTIFIER 16 AMPERES, 200 VOLTS



D<sup>2</sup>PAK  
CASE 418B  
STYLE 3

#### MARKING DIAGRAM



A = Assembly Location  
Y = Year  
WW = Work Week  
U1620 = Device Code  
G = Pb-Free Package  
AKA = Diode Polarity

#### ORDERING INFORMATION

| Device        | Package                         | Shipping†       |
|---------------|---------------------------------|-----------------|
| MURB1620CT    | D <sup>2</sup> PAK              | 50 Units/Rail   |
| MURB1620CTG   | D <sup>2</sup> PAK<br>(Pb-Free) | 50 Units/Rail   |
| MURB1620CTT4  | D <sup>2</sup> PAK              | 800/Tape & Reel |
| MURB1620CTT4G | D <sup>2</sup> PAK<br>(Pb-Free) | 800/Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

Preferred devices are recommended choices for future use and best overall value.

# MURB1620CT

## THERMAL CHARACTERISTICS (Per Leg)

| Rating                                                           | Symbol          | Value | Unit                 |
|------------------------------------------------------------------|-----------------|-------|----------------------|
| Maximum Thermal Resistance, Junction-to-Case                     | $R_{\theta JC}$ | 3     | $^{\circ}\text{C/W}$ |
| Maximum Thermal Resistance, Junction-to-Ambient                  | $R_{\theta JA}$ | 50    | $^{\circ}\text{C/W}$ |
| Temperature for Soldering Purposes: 1/8" from Case for 5 Seconds | $T_L$           | 260   | $^{\circ}\text{C}$   |

## ELECTRICAL CHARACTERISTICS (Per Leg)

| Characteristic                                                                                                                                                           | Symbol   | Max            | Unit          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|----------------|---------------|
| Maximum Instantaneous Forward Voltage (Note 1)<br>( $I_F = 8\text{ A}$ , $T_C = 150^{\circ}\text{C}$ )<br>( $I_F = 8\text{ A}$ , $T_C = 25^{\circ}\text{C}$ )            | $V_F$    | 0.895<br>0.975 | V             |
| Maximum Instantaneous Reverse Current (Note 1)<br>(Rated DC Voltage, $T_C = 150^{\circ}\text{C}$ )<br>(Rated DC Voltage, $T_C = 25^{\circ}\text{C}$ )                    | $I_R$    | 250<br>5       | $\mu\text{A}$ |
| Maximum Reverse Recovery Time<br>( $I_F = 1\text{ A}$ , $di/dt = 50\text{ A}/\mu\text{s}$ )<br>( $I_F = 0.5\text{ A}$ , $I_R = 1\text{ A}$ , $I_{REC} = 0.25\text{ A}$ ) | $t_{rr}$ | 35<br>25       | ns            |

1. Pulse Test: Pulse Width = 300  $\mu\text{s}$ , Duty Cycle  $\leq 2.0\%$




Figure 1. Typical Forward Voltage, Per Leg




Figure 2. Typical Reverse Current, Per Leg\*




Figure 3. Current Derating Case, Per Leg




Figure 4. Power Dissipation, Per Leg

# MURB1620CT




Figure 5. Thermal Response





Figure 6. Typical Capacitance, Per Leg

# MURB1620CT


## PACKAGE DIMENSIONS

D<sup>2</sup>PAK 3  
CASE 418B-04  
ISSUE J




- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
  2. CONTROLLING DIMENSION: INCH.
  3. 418B-01 THRU 418B-03 OBSOLETE, NEW STANDARD 418B-04.

| DIM | INCHES |       | MILLIMETERS |       |
|-----|--------|-------|-------------|-------|
|     | MIN    | MAX   | MIN         | MAX   |
| A   | 0.340  | 0.380 | 8.64        | 9.65  |
| B   | 0.380  | 0.405 | 9.65        | 10.29 |
| C   | 0.160  | 0.190 | 4.06        | 4.83  |
| D   | 0.020  | 0.035 | 0.51        | 0.89  |
| E   | 0.045  | 0.055 | 1.14        | 1.40  |
| F   | 0.310  | 0.350 | 7.87        | 8.89  |
| G   | 0.100  | BSC   | 2.54        | BSC   |
| H   | 0.080  | 0.110 | 2.03        | 2.79  |
| J   | 0.018  | 0.025 | 0.46        | 0.64  |
| K   | 0.090  | 0.110 | 2.29        | 2.79  |
| L   | 0.052  | 0.072 | 1.32        | 1.83  |
| M   | 0.280  | 0.320 | 7.11        | 8.13  |
| N   | 0.197  | REF   | 5.00        | REF   |
| P   | 0.079  | REF   | 2.00        | REF   |
| R   | 0.039  | REF   | 0.99        | REF   |
| S   | 0.575  | 0.625 | 14.60       | 15.88 |
| V   | 0.045  | 0.055 | 1.14        | 1.40  |



- STYLE 3:
1. PIN 1. ANODE
  2. CATHODE
  3. ANODE
  4. CATHODE

## SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

SWITCHMODE is a trademark of Semiconductor Components Industries, LLC.

**ON Semiconductor** and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 61312, Phoenix, Arizona 85082-1312 USA  
**Phone:** 480-829-7710 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 480-829-7709 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Japan:** ON Semiconductor, Japan Customer Focus Center  
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051  
**Phone:** 81-3-5773-3850

**ON Semiconductor Website:** <http://onsemi.com>

**Order Literature:** <http://www.onsemi.com/litorder>

For additional information, please contact your  
local Sales Representative.