

Description:

Fastener Length: 1-63/64"

NAS1097B5-32 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Rivet, Solid
NSN:	5320-01-067-3482
NIIN:	010673482
FSC:	Rivets / 5320
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets
Manufacturer Country:	United States

NAS1097B5-32 Specifications

Countersink Height:	0.0372 Inches Nominal
Countersink Angle:	100.0 Degrees Nominal
Fastener Length:	1.990 Inches Minimum And 2.010 Inches Maximum
Head Height:	0.003 Inches Minimum And 0.005 Inches Maximum
Head Minor Diameter:	0.185 Inches Minimum And 0.195 Inches Maximum
Head Major Diameter:	0.2469 Inches Maximum
Head Style:	Undersized Oval Countersunk
Material:	Aluminum Alloy 5056 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Shank Diameter:	0.155 Inches Minimum And 0.158 Inches Maximum
Shear Strength:	24000 Single Pounds Per Square Inch
Shank Style:	Straight
Specification/standard Data:	80205-nas1079 Professional/industrial Association Standard
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall
Surface Treatment:	Anodize Overall Or Chromate Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid-rivets/NAS1097B5-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.