

Description:

Fastener Length: 5/16", Thread: 6-32, Thread Length: 1/4", NAS1102 series screw

NAS1102E06-5 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Screw, Machine
NSN:	5305-00-213-8894
NIIN:	002138894
FSC:	Screws / 5305
Associated NSN(s):	• 5305-00-891-9035
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

NAS1102E06-5 Specifications

Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Fastener Length:	0.282 Inches Minimum And 0.312 Inches Maximum
Head Diameter:	0.231 Inches Minimum And 0.279 Inches Maximum
Head Style:	Flat Countersunk
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Diameter:	0.138 Inches
Internal Drive Style:	Torque Set
Screw Material Document And Classification:	Ams 5737 Assn Std Single Material Response
Screw Material:	Iron Alloy 660
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Screw Surface Treatment:	Passivate
Specification/standard Data:	80205-nas1102 Professional/industrial Association Standard
Thread Length:	0.162 Inches Minimum And 0.255 Inches Maximum
Thread Class:	3a
Thread Direction:	Right-hand
Thread Quantity Per Inch:	32
Thread Series Designator:	Unjc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine-screws/NAS1102E06-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.