

**Description:**

Fastener Length: 3/8", Thread: 6-32, Thread Length: 5/16

*NAS1102E06-6P Manufacturer certs (CofC) are provided free on all orders*

Order this part online

**Additional Information**

Gov. Issued Name:	Screw, Machine
NSN:	5305-00-007-9898
NIIN:	000079898
FSC:	Screws / 5305
Schedule B:	7318.15.2000, Bolts and bolts and their nuts or washers exported in the same shipment
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

# NAS1102E06-6P Specifications

<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Fastener Length:</b>	0.344 Inches Minimum And 0.375 Inches Maximum
<b>Head Diameter:</b>	0.231 Inches Minimum And 0.279 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Internal Drive Style:</b>	Torque Set
<b>Screw Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Specification/standard Data:</b>	80205-nas1102 Professional/industrial Association Standard
<b>Thread Length:</b>	0.225 Inches Minimum And 0.318 Inches Maximum
<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Quantity Per Inch:</b>	32
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine-screws/NAS1102E06-6P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.