

Description:

Fastener Length: 5/8", Thread: 10-32, Thread Length: 5/8"

NAS1191-3P10N Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Screw, Cap, Socket Head
NSN:	5305-00-850-6853
NIIN:	008506853
FSC:	Screws / 5305
Associated NSN(s):	• 5305-00-927-1294
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

NAS1191-3P10N Specifications

End Item Identification:	Aircraft;tf-56 Engine;aircraft, Hercules C-130;aircraft, Galaxy C-5;
Fastener Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Head Diameter:	0.306 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.103 Inches Minimum And 0.118 Inches Maximum
Head Style:	Flat Chamfer
Material:	Steel Comp 4037 Overall
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Diameter:	0.190 Inches
Internal Drive Style:	Cross Recess Type 1
Specification/standard Data:	80205-nas1192 Professional/industrial Association Standard
Surface Treatment Document And Classification:	Qq-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.562 Inches Minimum And 0.625 Inches Maximum
Thread Quantity Per Inch:	32
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine-screws/NAS1191-3P10N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.