

Description:

Fastener Length: 17/64", Thread: 3-56, Head Width: 15/32", Thread Length: 17/64"

NAS1351C03-4 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Screw, Cap, Socket Head
NSN:	5305-00-005-8210
NIIN:	000058210
FSC:	Screws / 5305
Associated NSN(s):	• 5305-01-089-2534
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

NAS1351C03-4 Specifications

Fastener Length:	0.234 Inches Minimum And 0.266 Inches Maximum
Hardness Rating:	80.0 Rockwell B Minimum Overall
Head Diameter:	0.154 Inches Minimum And 0.163 Inches Maximum
Head Height:	0.095 Inches Minimum And 0.099 Inches Maximum
Head Style:	Flat Chamfer
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 Overall
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Minimum Yield Strength:	30000 Pounds Per Square Inch
Nominal Thread Diameter:	0.099 Inches
Internal Drive Style:	Hexagon
Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard
Width Across Flats:	0.078 Inches Minimum And 0.479 Inches Maximum
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Surface Treatment:	Passivate Overall
Thread Length:	0.198 Inches Minimum And 0.266 Inches Maximum
Thread Class:	3a
Thread Direction:	Right-hand
Thread Quantity Per Inch:	56
Thread Series Designator:	Unf

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket-head-cap-screws/NAS1351C03-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.