

NAS1351N3-8 SOCKET HEAD CAP SCREW SPEC

Description:

Length: 31/64", Thread: 10-32, Head Width: 5/32", Thread Length: 27/64", NAS1351 series screw

NAS1351N3-8 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Screw, Cap, Socket Head
NSN:	5305-01-128-1576
NIIN:	011281576
FSC:	Screws / 5305
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

NAS1351N3-8 Specifications

Fastener Length:	0.470 Inches Minimum And 0.500 Inches Maximum
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Head Diameter:	0.303 Inches Minimum And 0.312 Inches Maximum
Head Height:	0.185 Inches Minimum And 0.190 Inches Maximum
Head Style:	Flat Chamfer
Material:	Iron Alloy 660 Overall
Minimum Yield Strength:	155000 Pounds Per Square Inch
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Diameter:	0.190 Inches
Internal Drive Style:	Hexagon
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas1351 Professional/Industrial Association Standard
Width Across Flats:	0.156 Inches Minimum And 0.159 Inches Maximum
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Surface Treatment:	Passivate Overall
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.408 Inches Minimum And 0.500 Inches Maximum
Thread Quantity Per Inch:	32
Thread Series Designator:	Unrf

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket-head-cap-screws/NAS1351N3-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.