

**Description:**

Fastener Length: 0-63/64", Thread: 6-32, Head Width: 7/64", Thread Length: 3/4", NAS1352 series screw

*NAS1352-06-16P Manufacturer certs (CofC) are provided free on all orders*

Order this part online

## Additional Information

Gov. Issued Name:	Screw, Cap, Socket Head
NSN:	5305-00-047-3146
NIIN:	000473146
FSC:	Screws / 5305
Associated NSN(s):	• 5305-01-016-4861
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

# NAS1352-06-16P Specifications

<b>Fastener Length:</b>	0.984 Inches Minimum And 1.016 Inches Maximum
<b>Hardness Rating:</b>	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
<b>Head Diameter:</b>	0.218 Inches Minimum And 0.226 Inches Maximum
<b>Head Height:</b>	0.134 Inches Minimum And 0.138 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Material:</b>	Steel Overall
<b>Minimum Yield Strength:</b>	155000 Pounds Per Square Inch
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Internal Drive Style:</b>	Hexagon
<b>Specification/standard Data:</b>	80205-nas1352 Professional/industrial Association Standard
<b>Width Across Flats:</b>	0.109 Inches Minimum And 0.111 Inches Maximum
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.750 Inches Minimum
<b>Thread Quantity Per Inch:</b>	32
<b>Thread Series Designator:</b>	Unrc

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket-head-cap-screws/NAS1352-06-16P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.