

Description:

Fastener Length: 3/4", Thread: 6-32, Head Width: 7/64", Thread Length: 3/4", NAS1352 series screw

NAS1352N06-12 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Screw, Cap, Socket Head
NSN:	5305-01-177-9730
NIIN:	011779730
FSC:	Screws / 5305
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

NAS1352N06-12 Specifications

Fastener Length:	0.720 Inches Minimum And 0.750 Inches Maximum
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Head Style:	Flat Chamfer
Material:	Iron Alloy 660 Overall
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Diameter:	0.138 Inches
Internal Drive Style:	Hexagon
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard
Width Across Flats:	0.1094 Inches Minimum And 0.1111 Inches Maximum
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Surface Treatment:	Passivate Overall
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.658 Inches Minimum And 0.750 Inches Maximum
Thread Quantity Per Inch:	32
Thread Series Designator:	Unrc

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket-head-cap-screws/NAS1352N06-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.