

# NAS1352N08-18 SOCKET HEAD SCREW SPEC

Military-Fasteners.com

#### **Description:**

Fastener Length: 1-1/8", Thread: 8-32, Head Width: 9/64", Thread Length: 7/8"

NAS1352N08-18 Manufacturer certs (CofC) are provided free on all orders

Order this part online

### **Additional Information**

Gov. Issued Name:	Screw, Cap, Socket Head
NSN:	5305-01-326-2694
NIIN:	013262694
FSC:	Screws / 5305
Schedule B:	7318.15.2000, Bolts and bolts and their nuts or washers exported in the same shipment
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

# NAS1352N08-18 Specifications

Fastener Length:	1.125 Inches Nominal
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Head Style:	Flat Chamfer
Material:	Iron Alloy 660 Overall
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Diameter:	0.164 Inches
Internal Drive Style:	Hexagon
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard
Width Across Flats:	0.1406 Inches Minimum And 0.1426 Inches Maximum
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Surface Treatment:	Passivate Overall
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Nominal
Thread Quantity Per Inch:	32
Thread Series Designator:	Unrc

## **How to Order**

Order this socket head screw from our inventory online by visiting <u>https://military-fasteners.com/screws/socket-head-cap-screws/NAS1352N08-18</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.