

## NAS1352N08-8 SOCKET HEAD CAP SCREW SPEC

**Description:** 

Fastener Length: 1/2", Thread: 8-32, Head Width: 9/64", Thread Length: 1/2", Flat chamfer head, NAS1352 series screw

NAS1352N08-8 Manufacturer certs (CofC) are provided free on all orders

Order this part online

## **Additional Information**

Gov. Issued Name: Screw, Cap, Socket Head

NSN: 5305-01-143-0596

NIIN: 011430596

FSC: Screws / *5305* Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093490, Bolt / Nut / Screw / Clips / Fastener / Etc

Manufacturer Country: United States

See page 2 for technical characteristics

## **NAS1352N08-8 Specifications**

Fastener Length:	0.470 Inches Minimum And 0.500 Inches Maximum
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Head Style:	Flat Chamfer
Material:	Iron Alloy 660 Overall
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Diameter:	0.164 Inches
Internal Drive Style:	Hexagon
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard
Width Across Flats:	0.141 Inches Minimum And 0.143 Inches Maximum
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Surface Treatment:	Passivate Overall
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.408 Inches Minimum And 0.500 Inches Maximum
Thread Quantity Per Inch:	32
Thread Series Designator:	Unrc

## **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket-head-cap-screws/NAS1352N08-8">https://military-fasteners.com/screws/socket-head-cap-screws/NAS1352N08-8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.