

Description:

Fastener Length: 3/16", Thread: 2-56, Thread Length: 3/16", NAS1635 series screw

NAS1635-02-3 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Screw, Machine
NSN:	5305-00-459-1147
NIIN:	004591147
FSC:	Screws / 5305
Schedule B:	7318.15.6080
ECCN:	9A991D
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

NAS1635-02-3 Specifications

Fastener Length:	0.158 Inches Minimum And 0.188 Inches Maximum
Head Diameter:	0.155 Inches Minimum And 0.167 Inches Maximum
Head Height:	0.053 Inches Minimum And 0.062 Inches Maximum
Head Style:	Pan
Nominal Thread Diameter:	0.086 Inches
Internal Drive Style:	Cross Recess Type 1
Screw Surface Treatment:	Passivate
Screw Material:	Steel Corrosion Resisting
Screw Surface Treatment Document And Classification:	Mil-f-14072,finish E300 Mil Spec Single Treatment Response
Specification/standard Data:	80205-nas1635 Professional/industrial Association Standard
Thread Length:	0.122 Inches Minimum And 0.188 Inches Maximum
Thread Class:	2a
Thread Direction:	Right-hand
Thread Quantity Per Inch:	56
Thread Series Designator:	Unc

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket-head-cap-screws/NAS1635-02-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.