

Description:

Fastener Length: 5/16", Thread: 6-32, Thread Length: 5/16"

NAS1635-06LE5 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Screw, Machine
NSN:	5305-00-321-9892
NIIN:	003219892
FSC:	Screws / 5305
Associated NSN(s):	• 5305-00-036-6732
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

NAS1635-06LE5 Specifications

Fastener Length:	0.282 Inches Minimum And 0.312 Inches Maximum
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Head Style:	Pan
Nominal Thread Diameter:	0.138 Inches
Internal Drive Style:	Cross Recess Type 1
Locking Feature Material:	Plastic Polyamide
Locking Feature:	Patch Or Pellet Or Strip
Screw Surface Treatment:	Passivate
Screw Material:	Steel Corrosion Resisting
Screw Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response
Specification/standard Data:	80205-nas1635 Professional/industrial Association Standard
Thread Length:	0.220 Inches Minimum And 0.312 Inches Maximum
Thread Class:	2a
Thread Direction:	Right-hand
Thread Quantity Per Inch:	32
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket-head-cap-screw/NAS1635-06LE5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.