

## NAS1669-08DL8 JO-BOLT SPEC

**Description:** 

Head Width: 1/4"

NAS1669-08DL8 Manufacturer certs (CofC) are provided free on all orders

Order this part online

## **Additional Information**

Gov. Issued Name: Rivet, Blind

NSN: 5320-01-340-6735

NIIN: 013406735

FSC: Rivets / 5320

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc

Manufacturer Country: United States

## **NAS1669-08DL8 Specifications**

| Expansion Device:                              | Break Stem                                                                                                                                            |
|------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Features Provided:                             | Drive Nut                                                                                                                                             |
| Grip Length:                                   | 0.470 Inches Minimum And 0.531 Inches Maximum                                                                                                         |
| Head Height:                                   | 0.268 Inches Maximum                                                                                                                                  |
| Head Style:                                    | Hexagon                                                                                                                                               |
| Material:                                      | Steel Comp 4130 Bolt Or Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt                                                                                  |
| Material:                                      | Steel Comp 4130 Nut Or Steel Comp 4140 Nut Or Steel Comp 8740 Nut                                                                                     |
| Material:                                      | Steel Comp 303 Sleeve Or Steel Comp 304 Sleeve Or Steel Comp 303se Sleeve                                                                             |
| Material Document And Classification:          | Astm A582 Assn Std 1st Material Response Sleeve Or Ams 5639 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve   |
| Material Document And Classification:          | Mil-s-6758 Mil Spec 1st Material Response Bolt Or Mil-s-5626 Mil Spec 2nd Material Response Bolt Or Mil-s-6049 Mil<br>Spec 3rd Material Response Bolt |
| Material Document And Classification:          | Mil-s-6758 Mil Spec 1st Material Response Nut Or Mil-s-5626 Mil Spec 2nd Material Response Nut Or Mil-s-6049 Mil Spec 3rd Material Response Nut       |
| Shank Diameter:                                | 0.1625 Inches Minimum And 0.1645 Inches Maximum                                                                                                       |
| Shank Style:                                   | Threaded Self-plugging Shank W/sleeve                                                                                                                 |
| Special Features:                              | Drive Nut Mild Steel Color Gold With Corrosion Retardent Coating                                                                                      |
| Specification/standard Data:                   | 80205-nas1669 Professional/industrial Association Standard                                                                                            |
| Width Across Flats:                            | 0.244 Inches Minimum And 0.250 Inches Maximum                                                                                                         |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec 1st Treatment Response Sleeve And Qq-p-416,ty1,cl3 Fed Spec 2nd Treatment Response Sleeve                                            |
| Surface Treatment Document And Classification: | Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Bolt                                                                                              |
| Surface Treatment Document And Classification: | Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Nut                                                                                               |
| Surface Treatment:                             | Cadmium Bolt And Chromate Bolt                                                                                                                        |
| Surface Treatment:                             | Cadmium Nut And Chromate Nut                                                                                                                          |
| Surface Treatment:                             | Passivate Sleeve And Cadmium Sleeve                                                                                                                   |

## **How to Order**

Order this jo-bolt from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind-rivets/NAS1669-08DL8">https://military-fasteners.com/rivets/blind-rivets/NAS1669-08DL8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind-rivets/NAS1669-08DL8">https://military-fasteners.com/rivets/blind-rivets/NAS1669-08DL8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1669-08DL8">https://military-fasteners.com/rivets/blind-rivets/NAS1669-08DL8</a> and selecting the quantity you want then