

Description:

Grip range: 0.595" - 0.656", diameter: 0.164", general purpose blind rivet - protruding head internally threaded - external sleeve

BAC Part Number:

BACB30CC5W10

NAS1669-08L10 Manufacturer certs (CofC) are provided free on all orders

[Order this part online](#)

**Additional Information**

Gov. Issued Name:	Blind Rivet
NSN:	5320-00-562-7398
NIIN:	005627398
FSC:	Rivets / 5320
Associated NSN(s):	• 5320-00-702-9291
Schedule B:	7318.23.0000, Rivets of iron or steel
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc
Manufacturer Country:	United States

NAS1669-08L10 Specifications

Expansion Device:	Threaded Stem
Grip Length:	0.595 Inches Minimum And 0.656 Inches Maximum
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Head Height:	0.096 Inches Maximum
Head Style:	Hexagon
Material:	Steel Comp 4140 Body Or Steel Comp 8740 Body Or Steel Comp 4130 Body
Material:	Steel Comp 304 Sleeve Or Steel Comp 303f Sleeve Or Steel Comp 303 Sleeve Or Steel Comp 304 Sleeve
Material:	Steel Comp 4140 Stem Or Steel Comp 8740 Stem Or Steel Comp 4130 Stem
Material Document And Classification:	Ams 5645 Assn Std Single Material Response Sleeve Or Ams 5641 Assn Std Single Material Response Sleeve Or Qq-s-764 Ty 303 Fed Spec Single Material Response Sleeve Or Qq-s-764 Ty 304 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Mil-s-5676 Mil Spec Single Material Response Body Or Mil-s-6049 Mil Spec Single Material Response Body Or Mil-s-6758 Mil Spec Single Material Response Body
Material Document And Classification:	Mil-s-5676 Mil Spec Single Material Response Stem Or Mil-s-6049 Mil Spec Single Material Response Stem Or Mil-s-6758 Mil Spec Single Material Response Stem
Shank Diameter:	0.1625 Inches Minimum And 0.1645 Inches Maximum
Shear Strength:	3355 Double Pounds Per Square Inch
Shank Style:	Threaded Self-plugging Shank W/sleeve
Specification/standard Data:	80205-nas1699 Professional/Industrial Association Standard
Width Across Flats:	0.244 Inches Minimum And 0.250 Inches Maximum
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec 1st Treatment Response Sleeve And Qq-p-416,ty 1,cl 3 Fed Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Body
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem
Surface Treatment:	Cadmium Body
Surface Treatment:	Passivate Sleeve Or Cadmium Sleeve
Surface Treatment:	Cadmium Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind-rivets/NAS1669-08L10> and selecting the quantity you want then

click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.