

**Description:**

Grip range: 0.532" - 0.594", diameter: 0.200", general purpose blind rivet - protruding head internally threaded - external sleeve

**BAC Part Number:**

BACB30CC6W9

*NAS1669-3L9 Manufacturer certs (CofC) are provided free on all orders*

[Order this part online](#)

**Additional Information**

Gov. Issued Name:	Blind Rivet
NSN:	5320-00-209-0234
NIIN:	002090234
FSC:	Rivets / 5320
Associated NSN(s):	<ul style="list-style-type: none"><li>• 5320-00-001-5154</li><li>• 5320-00-069-5629</li></ul>
Schedule B:	7318.23.0000, Rivets of iron or steel
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc
Manufacturer Country:	United States

# NAS1669-3L9 Specifications

<b>Expansion Device:</b>	Threaded Stem
<b>Grip Length:</b>	0.532 Inches Minimum And 0.594 Inches Maximum
<b>Hardness Rating:</b>	39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt
<b>Hardness Rating:</b>	39.0 Rockwell C Minimum Nut And 43.0 Rockwell C Maximum Nut
<b>Head Height:</b>	0.113 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Material:</b>	Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 Bolt
<b>Material:</b>	Steel Comp 4140 Nut Or Steel Comp 8740 Nut Or Steel Comp 4130 Nut
<b>Material:</b>	Steel Comp 304 Sleeve Or Steel Comp 303f Sleeve Or Steel Comp 303 Sleeve
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Nut Or Mil-s-6049 Mil Spec 2nd Material Response Nut Or Mil-s-6758 Mil Spec 3rd Material Response Nut
<b>Shank Diameter:</b>	0.197 Inches Minimum And 0.199 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Specification/standard Data:</b>	80205-nas1669 Professional/Industrial Association Standard
<b>Width Across Flats:</b>	0.305 Inches Minimum And 0.312 Inches Maximum
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Nut
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 1,cl 3 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response Sleeve
<b>Surface Treatment:</b>	Cadmium Bolt And Chromate Bolt
<b>Surface Treatment:</b>	Cadmium Nut And Chromate Nut
<b>Surface Treatment:</b>	Cadmium Sleeve And Passivate Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind-rivets/NAS1669-3L9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.