

Description:

Grip range: 0.345" - 0.406", diameter: 0.260", general purpose, protruding head internally threaded, external sleeve, jo bolt, NAS1669 series rivet

NAS1669-4L6 Manufacturer certs (CofC) are provided free on all orders

[Order this part online](#)



Additional Information

Gov. Issued Name:	Rivet, Blind
NSN:	5320-00-558-3431
NIIN:	005583431
FSC:	Rivets / 5320
Associated NSN(s):	• 5320-00-589-5403
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc
Manufacturer Country:	United States

NAS1669-4L6 Specifications

Expansion Device:	Threaded Mandrel
Fastener Length:	0.491 Inches Minimum And 0.521 Inches Maximum
Grip Length:	0.345 Inches Minimum And 0.406 Inches Maximum
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Head Height:	0.135 Inches Nominal
Head Style:	Hexagon
Material:	Steel Body
Material:	Steel Stem
Material:	Steel Corrosion Resisting Sleeve
Shank Diameter:	0.258 Inches Minimum And 0.260 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Shear Strength:	9000 Double Pounds Per Square Inch
Specification/standard Data:	80205-nas1669 Professional/Industrial Association Standard
Width Across Flats:	0.367 Inches Minimum And 0.375 Inches Maximum
Surface Treatment:	Cadmium Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind-rivets/NAS1669-4L6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.