



Military-Fasteners.com

NAS1726-3E SELF-LOCKING ASSEMBLED WASHER NUT SPEC

Description:

Thread: 10-32, self-locking nut with captive washer, NAS1726 series nut

NAS1726-3E Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Self-Locking Assembled Washer Nut
NSN:	5310-01-308-4822
NIIN:	013084822
FSC:	Nuts and Washers / 5310
Schedule B:	7318.16.0000
ECCN:	EAR99
National Motor Freight:	
Manufacturer Country:	United States

See page 2 for technical characteristics

NAS1726-3E Specifications

Bearing Surface Finish:	125.0 Microinches
Counterbore Diameter:	0.211 Inches Minimum Nut And 0.221 Inches Maximum Nut
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Material:	Steel Comp 8740 Overall
Nominal Thread Size:	0.190 Inches
Nut Style:	Flat With Turned Up Edge
Overall Height:	0.223 Inches Minimum And 0.243 Inches Maximum
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Specification/standard Data:	80205-nas1726 Professional/Industrial Association Standard
Washer Outside Diameter:	0.380 Inches Maximum
Width Across Flats:	0.213 Inches Minimum And 0.221 Inches Maximum
Surface Treatment:	Cadmium Overall
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Class:	3b
Thread Direction:	Right-hand
Thread Quantity Per Inch:	32
Thread Series:	Unjf

How to Order

Order this self-locking assembled washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking-assembled-washer-nuts/NAS1726-3E and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.