



Military-Fasteners.com

NAS1726-4E SELF-LOCKING ASSEMBLED WASHER NUT SPEC

Description:

Thread: 1/4-28, steel alloy, locknut with captive washer, NAS1726 series nut

NAS1726-4E Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Self-Locking Assembled Washer Nut
NSN:	5310-01-139-3286
NIIN:	011393286
FSC:	Nuts and Washers / 5310
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	
Manufacturer Country:	United States

See page 2 for technical characteristics

NAS1726-4E Specifications

Hardness Rating:	36.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
Material:	Steel Comp 8740 Overall
Nominal Thread Size:	0.250 Inches
Nut Counterbore Depth:	0.072 Inches Minimum Overall And 0.087 Inches Maximum Overall
Nut Style:	Flat With Turned Up Edge
Overall Height:	0.271 Inches Minimum And 0.291 Inches Maximum
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Soluble Lubricant
Specification/standard Data:	80205-nas1726 Professional/industrial Association Standard
Washer Outside Diameter:	0.460 Inches Maximum
Width Across Flats:	0.274 Inches Minimum And 0.284 Inches Maximum
Surface Treatment:	Cadmium Overall
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Class:	2b
Thread Direction:	Right-hand
Thread Quantity Per Inch:	28
Thread Series:	Unjf

How to Order

Order this self-locking assembled washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking-assembled-washer-nuts/NAS1726-4E and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.