

NAS1789-3K PLATE LOCKNUT SPEC

Military-Fasteners.com

Description:

Thread Size: 1/4", Nut Length: 1/2", Nut Height: 1/4"

NAS1789-3K Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Nut, Self-locking, Plate
5310-01-306-4861
013064861
Nuts and Washers / 5310
7318.16.0000, Nuts of iron or steel
194160, Washer Or Gaskets, Iron Or Steel,
United States

NAS1789-3K Specifications

Distance From Centerline To Flat:	0.175 Inches Nominal
Center To Center Distance Between Mounting Holes Along Width:	0.217 Inches Minimum And 0.221 Inches Maximum
Features Provided:	Floating Nut
Material Document And Classification:	Sae 103 0 Assn Std Single Material Response Overall
Material:	Steel Comp 1030 Overall
Mounting Hole Arrangement Style:	2 Holes
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nominal Thread Size:	0.190 Inches
Nut Length:	0.525 Inches Nominal
Nut Height:	0.250 Inches Nominal
Nut Mounting Provision:	Dimpled Holes
Nut Style:	Plate
Overall Height:	0.250 Inches Maximum
Lubrication:	Dry Film Lubricant
Plate Thickness:	0.032 Inches Nominal
Plate Width:	0.490 Inches Nominal
Specification/standard Data:	80205-nas1789 Professional/industrial Association Standard
Special Features:	Sulfur And Phosphorus Content Shall Not Exceed 30by Weight
Surface Treatment Document And Classification:	Qq-p-416, Ty 2, Cl 2 Fed Spec Single Treatment Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Class:	3b
Thread Direction:	Right-hand
Thread Quantity Per Inch:	32
Thread Series:	Unjf

How to Order

Order this plate locknut from our inventory online by visiting <u>https://military-fasteners.com/nuts/self_locking-nutplates/NAS1789-3K</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.

Provided by Military-Fasteners.com