

NAS1791C3-2 SELF-LOCKING NUTPLATE SPEC

Description:

Thread Size: 3/16", Nut Length: 15/16", Nut Height: 9/32", two lug, NAS1791 series nut

NAS1791C3-2 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Nut, Self-locking, Plate
NSN:	5310-00-143-0358
NIIN:	001430358
FSC:	Nuts and Washers / 5310
Associated NSN(s):	• 5310-01-332-3248
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

NAS1791C3-2 Specifications

Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Counterbore Diameter:	0.194 Inches Minimum Nut And 0.207 Inches Maximum Nut
Distance From Aperture Center To Mounting Hole Center:	0.339 Inches Minimum And 0.349 Inches Maximum
Features Provided:	Floating Nut
Material:	Steel Corrosion Resisting Overall
Mounting Hole Arrangement Style:	2 Holes
Mounting Hole Diameter:	0.093 Inches Minimum And 0.103 Inches Maximum
Nominal Thread Size:	0.190 Inches
Nut Counterbore Depth:	0.100 Inches Minimum Nut
Nut Length:	0.948 Inches Maximum
Nut Height:	0.296 Inches Nominal
Nut Mounting Provision:	Straight Holes
Nut Style:	Plate
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Plate Thickness:	0.032 Inches Nominal
Plate Width:	0.440 Inches Nominal
Special Features:	Plate U Shpae 0.220 In. High,one Hole Each Side To Hold Retaining Clip
Surface Treatment:	Passivate Overall
Thread Class:	3b
Thread Direction:	Right-hand
Thread Quantity Per Inch:	32
Thread Series:	Unjf

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking-nutplates/NAS1791C3-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.