

NAS1791C4-1 SELF-LOCKING NUTPLATE SPEC

Description:

Fine thread, floating nut, two holes, NAS1791 series nut

NAS1791C4-1 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Self-Locking Plate Nut
NSN:	5310-00-283-4618
NIIN:	002834618
FSC:	Nuts and Washers / 5310
Associated NSN(s):	• 5310-01-090-5557
Schedule B:	7318.16.0000
ECCN:	9A991.d
National Motor Freight:	013540, Alum Nuts
Manufacturer Country:	United States

NAS1791C4-1 Specifications

Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Counterbore Diameter:	0.254 Inches Minimum Nut
Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Features Provided:	Floating Nut
Material:	Iron Alloy 660 Shell
Mounting Hole Arrangement Style:	2 Holes
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nominal Thread Size:	0.250 Inches
Nut Counterbore Depth:	0.070 Inches Minimum Nut
Nut Length:	1.292 Inches Maximum
Nut Height:	0.286 Inches Maximum
Nut Mounting Provision:	Straight Holes
Nut Style:	Plate
Locking Feature:	Prevailing Torque All Metal Design
Material Document And Classification:	Ams5735 Assn Std Single Material Response Shell
Plate Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Plate Width:	0.574 Inches Nominal
Specification/standard Data:	76301-st3-443 Manufacturers Standard
Surface Treatment:	Passivate Shell
Thread Class:	3b
Thread Direction:	Right-hand
Thread Quantity Per Inch:	28
Thread Series:	Unjf

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking-nutplates/NAS1791C4-1 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.