

Description:

NAS1919 series rivet

NAS1919C06S04U Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Rivet, Blind
NSN:	5320-01-476-4790
NIIN:	014764790
FSC:	Rivets / 5320
Schedule B:	7318.23.0000, Rivets of iron or steel
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed
Manufacturer Country:	United States

NAS1919C06S04U Specifications

End Item Identification:	F16aircombfit; F-16 Aircraft
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Head Style:	Universal
Material:	Iron Alloy 660 Locking Ring Or Steel Comp 316 Locking Ring
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams5737 Assn Std Single Material Response Locking Ring Or Ams5690 Assn Std Single Material Response Locking Ring
Material Document And Classification:	Ams5737 Assn Std Single Material Response Sleeve
Material Document And Classification:	Ams5737 Assn Std Single Material Response Stem
Shank Diameter:	0.190 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Specification/standard Data:	80205-nas1919 Professional/Industrial Association Standard
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Ring
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Sleeve Or Qq-p-416, Ty li, Cl3 Fed Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Surface Treatment:	Passivate Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind-rivets/NAS1919C06S04U> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.