

NAS624-14 SHEAR BOLT SPEC

Description:

Length: 1.360", grip: 0.875", thread: 1/4-28, twelve point external wrenching bolt - cadmium plated steel

NAS624-14 Manufacturer certs (CofC) are provided free on all orders

Order this part online



Additional Information

Gov. Issued Name: Shear Bolt

NSN: 5306-00-543-4628

NIIN: 005434628 FSC: Bolts / *5306*

Schedule B: 7318.15.2000, Bolts and bolts and their nuts or washers exported in the same shipment

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)

Manufacturer Country: United States

NAS624-14 Specifications

Extended Washer Diameter:	0.433 Inches Nominal
Extended Washer Thickness:	0.069 Inches Nominal
Fastener Length:	1.345 Inches Minimum And 1.375 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Grip Length:	0.855 Inches Minimum And 0.865 Inches Maximum
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Head Height:	0.300 Inches Nominal
Head Style:	Double Hexagon W/hole
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Nominal Thread Diameter:	0.250 Inches
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Material Document And Classification: Specification/standard Data:	3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material
	3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Specification/standard Data:	3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall 80205-nas624 Professional/industrial Association Standard
Specification/standard Data: Width Between Flats: Surface Treatment Document And	3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall 80205-nas624 Professional/industrial Association Standard 0.306 Inches Minimum And 0.315 Inches Maximum
Specification/standard Data: Width Between Flats: Surface Treatment Document And Classification:	3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall 80205-nas624 Professional/industrial Association Standard 0.306 Inches Minimum And 0.315 Inches Maximum Nas 672 Assn Std Single Treatment Response Overall
Specification/standard Data: Width Between Flats: Surface Treatment Document And Classification: Surface Treatment:	3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall 80205-nas624 Professional/industrial Association Standard 0.306 Inches Minimum And 0.315 Inches Maximum Nas 672 Assn Std Single Treatment Response Overall Cadmium Overall
Specification/standard Data: Width Between Flats: Surface Treatment Document And Classification: Surface Treatment: Thread Class:	3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall 80205-nas624 Professional/industrial Association Standard 0.306 Inches Minimum And 0.315 Inches Maximum Nas 672 Assn Std Single Treatment Response Overall Cadmium Overall 3a
Specification/standard Data: Width Between Flats: Surface Treatment Document And Classification: Surface Treatment: Thread Class: Thread Direction:	3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall 80205-nas624 Professional/industrial Association Standard 0.306 Inches Minimum And 0.315 Inches Maximum Nas 672 Assn Std Single Treatment Response Overall Cadmium Overall 3a Right-hand
Specification/standard Data: Width Between Flats: Surface Treatment Document And Classification: Surface Treatment: Thread Class: Thread Direction: Thread Length:	3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall 80205-nas624 Professional/industrial Association Standard 0.306 Inches Minimum And 0.315 Inches Maximum Nas 672 Assn Std Single Treatment Response Overall Cadmium Overall 3a Right-hand 0.460 Inches Minimum And 0.510 Inches Maximum

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear-bolts/NAS624-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear-bolts/NAS624-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear-bolts/NAS624-14 and selecting the quantity you want then click "add to cart".