

Description:

Fastener Length: 19/64", Thread: 10-32, Thread Length: 19/64"

NAS8003-5 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Screw, Machine
NSN:	5305-00-728-7693
NIIN:	007287693
FSC:	Screws / 5305
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

NAS8003-5 Specifications

Fastener Length:	0.280 Inches Minimum And 0.310 Inches Maximum
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Head Style:	Pan
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Diameter:	0.190 Inches
Internal Drive Style:	Cross Recess Type 1
Screw Material:	Steel
Screw Surface Treatment Document And Classification:	Qq-p-416,ty2 Cl3 Fed Spec Single Treatment Response
Screw Surface Treatment:	Cadmium And Chromate
Specification/standard Data:	80205-nas603 Professional/industrial Association Standard
Thread Length:	0.218 Inches Minimum And 0.310 Inches Maximum
Thread Class:	3a
Thread Direction:	Right-hand
Thread Quantity Per Inch:	32
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine-screws/NAS8003-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.