

Description:

Fastener Length: 35/64", Thread: 10-32, Thread Length: 35/64"

NAS8303-9 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Screw, Machine
NSN:	5305-01-269-7816
NIIN:	012697816
FSC:	Screws / 5305
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

NAS8303-9 Specifications

Extended Washer Diameter:	0.397 Inches Nominal
Extended Washer Thickness:	0.115 Inches Minimum And 0.142 Inches Maximum
Fastener Length:	0.530 Inches Minimum And 0.560 Inches Maximum
Head Diameter:	0.353 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.085 Inches Minimum And 0.105 Inches Maximum
Head Style:	Round Extended Washer
Nominal Thread Diameter:	0.190 Inches
Internal Drive Style:	Cross Recess Type 1
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams6322 Assn Std 3rd Material Response
Screw Material:	Steel Comp 4340 Or Steel Comp 8740
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.530 Inches Minimum And 0.560 Inches Maximum
Thread Quantity Per Inch:	32
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine-screws/NAS8303-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.