

Description

length: 0.511", grip: 0.188", thread: 8-32, 100°, reduced head close tolerance bolt - short thread - philips recess - cadmium plated alloy steel"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS86023
Minimum Qty (MOQ):	100
NSN:	5305-01-582-4805



* See page 2 for technical characteristics

P/N NAS8602-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.501 Inches Minimum And 0.520 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.226 Inches Minimum And 0.257 Inches Maximum
Grip Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.188 Inches Nominal
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty 2, Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS8602-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.