

Description:

Length: 0.385", grip: 0.062", thread: 10-32, 100°, reduced head close tolerance bolt - short thread - philips recess - cadmium plated alloy steel"

NAS8603-1 Manufacturer certs (CofC) are provided free on all orders

Order this part online



Additional Information

Gov. Issued Name:	Close Tolerance Screw
NSN:	5305-01-533-4729
NIIN:	015334729
FSC:	Screws / 5305
Schedule B:	7318.15.2000, Bolts and bolts and their nuts or washers exported in the same shipment
National Motor Freight:	
Manufacturer Country:	United States

NAS8603-1 Specifications

Fastener Length:	0.385 Inches Nominal
Grip Length:	0.062 Inches Nominal
Head Diameter:	0.266 Inches Minimum And 0.303 Inches Maximum
Head Style:	Flat Countersunk
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall And Ams6322 Assn Std 2nd Material Response Overall And Mil-s-6049 Mil Spec 2nd Material Response Overall
Part Name Assigned By Controlling Agency:	Bolt, 100degree Reduced Head, Phillips Recess, Close Tolerance, Alloy Steel, Short Thread
Specification/standard Data:	80205-nas8603 Professional/industrial Association Standard
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec All Treatment Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Class:	Aal
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Thread Quantity Per Inch:	32
Thread Series Designator:	Unjf

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close-tolerance-screws/NAS8603-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.